



TP-Link SX6632YF netwerk-switch Managed L2+/L3 Zwart

Merk : TP-Link

Artikelcode: SX6632YF

Productnaam : SX6632YF

TP-Link SX6632YF. Switch type: Managed, Switch-laag: L2+/L3. Console port: RJ-45. MAC-adrestabel: 128000 entries, Switchingcapaciteit: 820 Gbit/s. Netwerkstandaard: IEEE 802.1Q, IEEE 802.1ad, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3ah. Rack-montage



Beheerfuncties		Beveiliging	
Switch type *	Managed	SSH/SSL support	✓
Switch-laag	L2+/L3	Multicast-functies	
Quality of Service (QoS)	✓	Multicast-ondersteuning	✓
Web-gebaseerd management	✓	Protocollen	
Cloud-beheerd	✓	Beheerprotocollen	SNMPv1/v2c/v3
ARP-inspectie	✓	Design	
Poorten & interfaces		Rack-montage *	✓
Type basis-switching RJ-45 Ethernet-poorten *	✗	Stapelbaar *	✓
Aantal moduleslots SPF	6	Kleur van het product	Zwart
Aantal moduleslots SPF+	26	Aantal ventilatoren	4 ventilator(en)
Aantal USB Type-A-poorten	2	Prestatie	
Aantal USB-Type-C-poorten	1	Minimale systeemeisen	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ / Windows 7/8/10/11, MAC® OS, NetWare®, UNIX® /Linux.
Aantal beheerpoorten	1 stuk(s)	Energie	
Console port	RJ-45	Stroombron *	AC
Netwerk		Redundante voeding	✓
Netwerkstandaard *	IEEE 802.1Q, IEEE 802.1ad, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3ah	Aantal voedingen	2
10G support *	✓	AC-ingangsspanning	100 - 240 V
Port mirroring	✓	AC-ingangsfrequentie	50/60 Hz
IP routing	✓	Power over Ethernet (PoE)	
VLAN=ondersteuning	✓	Power over Ethernet (PoE) *	✗
Virtuele LAN-functies	MAC address-based VLAN, Multicast VLAN, Private VLAN, Protocol-based VLAN, Voice VLAN	Eisen aan de omgeving	
Data-uitwisseling		Bedrijfstemperatuur (T-T)	-5 - 40 °C
Switchingcapaciteit *	820 Gbit/s	Temperatuur bij opslag	-40 - 70 °C
Verzending snelheid	610,1 Mpps	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
MAC-adrestabel *	128000 entries	Luchtvochtigheid bij opslag	5 - 90 procent
Jumbo Frames ondersteuning	✓		
Jumbo frames	9000		
Packet buffergeheugen	8 MB		

Beveiliging		Gewicht en omvang	
DHCP-functies	DHCP Option 82	Breedte	440 mm
Access Control List (ACL)	✓	Diepte	380 mm
IGMP snooping	✓	Hoogte	44 mm
MAC adres filtering	✓	Verpakking	
Statische poort beveiliging	✓	Meegeleverde kabels	Stroom
		Snelstartgids	✓
		Rekbevestigingspakket	✓



4895252501315

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-JUN-2024. Prints or copies of Information are only valid on the printed Publication date