

ZYXEL

Zyxel XGS4600-32 Managed L3 Gigabit Ethernet (10/100/1000) Zwart



Merk : Zyxel

Artikelcode: XGS4600-32-ZZ0102F

Productnaam : XGS4600-32

Zyxel XGS4600-32. Switch type: Managed, Switch-laag: L3. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 24, Console port: RS-232. MAC-adrestabel: 32000 entries, Switchingcapaciteit: 136 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ad, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack-montage

Beheerfuncties		Design	
Switch type *	Managed	Rack-montage *	✓
Switch-laag	L3	Kleur van het product	Zwart
Quality of Service (QoS)	✓	Veiligheid	ANSI/UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1
MIB-ondersteuning	✓	Certificering	FCC Part 15 (Class A) CE EMC (Class A)
Poorten & interfaces		Prestatie	
Aantal basis-switching RJ-45 Ethernet-poorten *	24	Intern geheugen	1000 MB
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Flash memory	64 MB
Aantal Combo SFP-poorten	4	Geluidsniveau	59,8 dB
Aantal moduleslots SPF+	4	Mean time between failures (MTBF)	860610,82 uur
Console port	RS-232	Energie	
Netwerk		AC-ingangsspanning	100 - 240 V
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ad, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC-ingangsfrequentie	50 - 60 Hz
		Vermogensverbruik (max)	47 W
10G support *	✓	Power over Ethernet (PoE)	
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) *	✗
IP routing	✓	Eisen aan de omgeving	
Routing entries	12000	Bedrijfstemperatuur (T-T)	0 - 50 °C
Datastroombeheer	✓	Temperatuur bij opslag	-40 - 70 °C
Verbindingsaggregatie	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 95 procent
Spanning tree protocol	✓	Luchtvochtigheid bij opslag	10 - 95 procent
VLAN=ondersteuning	✓	Warmtedissipatie	160,27 BTU/h
Virtuele LAN-functies	Tagged VLAN	Gewicht en omvang	
Data-uitwisseling		Breedte	441 mm
Switchingcapaciteit *	136 Gbit/s	Diepte	270 mm
Throughput	101,1 Mpps	Hoogte	44 mm
MAC-adrestabel *	32000 entries	Gewicht	3,96 kg
Aantal IP-interfaces	256	Verpakking	
Packet buffergeheugen	4 MB	Rekbevestigingspakket	✓
Beveiliging		Breedte verpakking	616 mm
IGMP snooping	✓	Diepte verpakking	335 mm
Ondersteunde beveiligingsalgoritmen	SSH, SSH-2, SSL/TLS	Hoogte verpakking	107 mm
Authenticatie	Poortgebaseerde authenticatie	Gewicht verpakking	5,69 kg
Multicast-functies		Logistieke gegevens	
Multicast-ondersteuning	✓	Code geharmoniseerd systeem (HS)	85176990



4718937590513



0760559123567



760559123567

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-MAY-2023. Prints or copies of Information are only valid on the printed Publication date