

ZYXEL

Zyxel GS1350-12HP-EU0101F netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grijs

Merk : Zyxel

Artikelcode: GS1350-12HP-EU0101F

Productnaam : GS1350-12HP-EU0101F



- Met NebulaFlex Pro kunnen gebruikers in combinatie met Pro Pack voor 1 jaar flexibel wisselen tussen standalone-beheer en Nebula-cloudbeheer
- Standalone: Eenvoudig beheer en gemakkelijke installatie met de webgebaseerde GUI
- Nebula Cloud: Nebula Cloud maakt eenvoudige implementatie en flexibel netwerkbeheer mogelijk zonder dat daarvoor software of een controller moet worden geïnstalleerd
- Groot stroombudget

GS1350-12HP, 12 Port managed CCTV PoE switch, long range, 130W

Zyxel GS1350-12HP-EU0101F. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45

Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 10.

MAC-adrestabel: 8000 entries, Switchingcapaciteit: 24 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE.... Power over Ethernet (PoE). Rack-montage



Beheerfuncties		Beveiliging			
Switch type *	Managed	Algoritmen wachtrijplanning	SPQ, WFQ, Weighted Round Robin (WRR)		
Switch-laag	L2				
Web-gebaseerd management	✓	Multicast-functies			
Locatie-instellingen (CLI) configureren	✓	Multicast-ondersteuning	✓		
System event log	✓	Design			
MIB-ondersteuning	RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011, 2012, 2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4293, RFC 4292, RFC 4022, RFC 4113	Rack-montage *	✓		
		Kleur van het product	Grijs		
		LED-indicatoren	✓		
		Prestatie			
Poorten & interfaces		Geluidsniveau	27,3 dB		
		Upgraden van firmware mogelijk	✓		
		Mean time between failures (MTBF)	1065025,45 uur		
Netwerk		Energie			
		AC-ingangsspanning	100 - 240 V		
		AC-ingangsfrequentie	50 - 60 Hz		
		Vermogensverbruik (max)	160,3 W		
Netwerkstandaard *		Power over Ethernet (PoE)			
		Power over Ethernet (PoE) *	✓		
		Hoeveelheid Power over Ethernet (PoE) ports	8		
		Totaal Power over Ethernet (PoE)-budget	130 W		
10G support *		Eisen aan de omgeving			
		Bedrijfstemperatuur (T-T)	-20 - 50 °C		
		Temperatuur bij opslag	-40 - 70 °C		
		Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent		
Koperen ethernetbekabelingstechnologie		Luchtvochtigheid bij opslag	5 - 95 procent		
		Warmtedissipatie	546,62 BTU/h		
		Port mirroring		✓	
Datastroombeheer		✓			
				Broadcast stormbeheer	
Spanning tree protocol		✓			
				VLAN=ondersteuning	
Virtuele LAN-functies		MAC address-based VLAN, Port-based VLAN			
				Aantal VLANs	

Optische vezel		Gewicht en omvang	
Fiber ethernet cabling technologie	1000BASE-X	Breedte	267 mm
Data-uitwisseling		Diepte	162 mm
Switchingcapaciteit *	24 Gbit/s	Hoogte	44 mm
Verzending snelheid	17,8 Mpps	Gewicht	1,63 kg
MAC-adrestabel *	8000 entries	Verpakking	
Packet buffergeheugen	0,525 MB	Meegeleverde kabels	AC
Beveiliging		Rekbevestigingspakket	✓
		Logistieke gegevens	
DHCP-functies	DHCP client, DHCP relay, DHCP snooping	Code geharmoniseerd systeem (HS) 85176990	
IGMP snooping	✓		
IGMP-proxy	✓		
Ondersteunde beveiligingsalgoritmen	SNMP, SNMPv3, SSH, SSL/TLS		
MAC adres filtering	✓		
Bescherming lus	✓		



4718937604388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAY-2023. Prints or copies of Information are only valid on the printed Publication date