

Zyxel XS1930-12F-ZZ0101F netwerk-switch Managed L2/L3 Zwart



Merk : Zyxel

Artikelcode: XS1930-12F-ZZ0101F

Productnaam : XS1930-12F-ZZ0101F

Zyxel XS1930-12F-ZZ0101F. Switch type: Managed, Switch-laag: L2/L3. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 240 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3z. Netstekker: AC-in-aansluiting. Rack-montage

Beheerfuncties		Beveiliging	
Switch type *	Managed	Ondersteunde beveiligingsalgoritmen	HTTPS, SHA-2, SSL/TLS
Switch-laag	L2/L3	SSH/SSL support	✓
Quality of Service (QoS)	✓	Bescherming lus	✓
Web-gebaseerd management	✓	Multicast-functies	
ARP-inspectie	✓	Multicast-ondersteuning	✓
Locatie-instellingen (CLI) configureren	✓	Design	
MIB-ondersteuning	✓	Rack-montage *	✓
Poorten & interfaces		Kleur van het product	Zwart
Aantal moduleslots SPF+	10	LED-indicatoren	✓
Netstekker	AC-in-aansluiting	Prestatie	
Netwerk		Intern geheugen	256 MB
Netwerkstandaard *	IEEE 802.1p, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3z	Flash memory	32 MB
10G support *	✓	Energie	
Port mirroring	✓	Stroombron *	AC
Datastroombeheer	✓	AC-ingangsspanning	100 - 240 V
Verbindingsaggregatie	✓	AC-ingangsfrequentie	50 - 60 Hz
Broadcast stormbeheer	✓	Vermogensverbruik (max)	24,9 W
Spanning tree protocol	✓	Power over Ethernet (PoE)	
Ethernet LAN, data-overdrachtsnelheden	1000,2500,5000,10000 Mbit/s	Power over Ethernet (PoE) *	✗
VLAN=ondersteuning	✓	Eisen aan de omgeving	
Aantal VLANs	4000	Bedrijfstemperatuur (T-T)	-20 - 50 °C
Data-uitwisseling		Temperatuur bij opslag	-40 - 70 °C
Switchingcapaciteit *	240 Gbit/s	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Verzending snelheid	178,5 Mpps	Luchtvochtigheid bij opslag	5 - 95 procent
MAC-adrestabel *	16000 entries	Warmtedissipatie	84,91 BTU/h
Statische route	✓	Gewicht en omvang	
Jumbo Frames ondersteuning	✓	Breedte	484 mm
Jumbo frames	12000	Diepte	337 mm
Packet buffergeheugen	2 MB	Hoogte	79 mm
Beveiliging		Gewicht	3,63 kg
DHCP-functies	DHCP client, DHCP relay	Logistieke gegevens	
Access Control List (ACL)	✓	Code geharmoniseerd systeem (HS)	85176990
IGMP snooping	✓		



4718937620791

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAY-2023. Prints or copies of Information are only valid on the printed Publication date