

## Zyxel GS1915-8 Managed L2 Gigabit Ethernet (10/100/1000) Zwart

**Merk :** Zyxel

**Artikelcode:** GS1915-8-EU0101F

**Productnaam :** GS1915-8

- Compacte, betaalbare cloudswitching oplossing, wordt geleverd met 8 Gigabit-poorten
- Alle 8 poorten ondersteunen 802.3at PoE+, met een totaal vermogen van 60 W
- Ondersteunt Nebula en biedt zo een uniforme cloudnetwerkervaring, met bedraad, draadloos tot beveiligingsgateway
- Het is eenvoudig om de switch aan te sluiten, realtime configuraties te maken en overal en altijd toegang te hebben tot al je cloudapparaten via Nebula APP
- Slank en ventilatorloos ontwerp zorgt voor de stilste werking in elke werkomgeving

GS1915-8, 8-port GbE Smart Managed Switch

Zyxel GS1915-8. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 8. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 16 Gbit/s. Netwerkstandaard: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE.... Netstekker: AC-in-aansluiting



| Beheerfuncties                                  |                                                                                                                                                   | Design                                 |                                                  |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|--------------------------------------------------|
| Switch type *                                   | Managed                                                                                                                                           | Kleur van het product                  | Zwart                                            |
| Switch-laag                                     | L2                                                                                                                                                | LED-indicatoren                        | ✓                                                |
| Quality of Service (QoS)                        | ✓                                                                                                                                                 | Elektromagnetische compatibiliteit     | LVD EN60950-1, BSMI CNS14336-1                   |
| Web-gebaseerd management                        | ✓                                                                                                                                                 | Certificering                          | CE, FCC, C-Tick, Class A, Class B, BSMI CNS13438 |
| System event log                                | ✓                                                                                                                                                 |                                        |                                                  |
| MIB-ondersteuning                               | RFC 1213 MIB II, RFC 2819, RFC 1215, RFC 1493                                                                                                     |                                        |                                                  |
| Poorten & interfaces                            |                                                                                                                                                   | Prestatie                              |                                                  |
| Aantal basis-switching RJ-45 Ethernet-poorten * | 8                                                                                                                                                 | Mean time between failures (MTBF)      | 1144461 uur                                      |
| Type basis-switching RJ-45 Ethernet-poorten *   | Gigabit Ethernet (10/100/1000)                                                                                                                    |                                        |                                                  |
| Aantal Gigabit Ethernet (koper)-poorten         | 8                                                                                                                                                 | Energie                                |                                                  |
| Netstekker                                      | AC-in-aansluiting                                                                                                                                 | Stroombron *                           | AC                                               |
| Netwerk                                         |                                                                                                                                                   | AC-ingangsspanning                     | 220 - 240 V                                      |
|                                                 | IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | AC-ingangsfrequentie                   | 50 - 60 Hz                                       |
| Netwerkstandaard *                              |                                                                                                                                                   | Vermogensverbruik (max)                | 4,7 W                                            |
| 10G support *                                   | ✗                                                                                                                                                 | Power over Ethernet (PoE)              |                                                  |
| Koperen ethernetbekabelingstechnologie          | 10BASE-T, 100BASE-TX, 1000BASE-T                                                                                                                  | Power over Ethernet (PoE) *            | ✗                                                |
| Full duplex                                     | ✓                                                                                                                                                 | Eisen aan de omgeving                  |                                                  |
| Datastroombeheer                                | ✓                                                                                                                                                 | Bedrijfstemperatuur (T-T)              | 0 - 40 °C                                        |
| Broadcast stormbeheer                           | ✓                                                                                                                                                 | Temperatuur bij opslag                 | -40 - 70 °C                                      |
| Rate limiting                                   | ✓                                                                                                                                                 | Relatieve vochtigheid in bedrijf (V-V) | 10 - 95 procent                                  |
| Auto MDI/MDI-X                                  | ✓                                                                                                                                                 | Luchtvochtigheid bij opslag            | 10 - 95 procent                                  |
| VLAN-ondersteuning                              | ✓                                                                                                                                                 | Warmte-dissipatie                      | 16,03 BTU/h                                      |
| Aantal VLANs                                    | 8                                                                                                                                                 | Gewicht en omvang                      |                                                  |
| Data-uitwisseling                               |                                                                                                                                                   | Breedte                                | 250 mm                                           |
| Switchingcapaciteit *                           | 16 Gbit/s                                                                                                                                         | Diepte                                 | 104 mm                                           |
| Verzending snelheid                             | 11,9 Mpps                                                                                                                                         | Hoogte                                 | 27 mm                                            |
|                                                 |                                                                                                                                                   | Gewicht                                | 620 g                                            |
|                                                 |                                                                                                                                                   | Verpakking                             |                                                  |
|                                                 |                                                                                                                                                   | Meegeleverde kabels                    | AC                                               |
|                                                 |                                                                                                                                                   | Snelstartgids                          | ✓                                                |
|                                                 |                                                                                                                                                   | Gebruiksaanwijzing                     | ✓                                                |

| Data-uitwisseling          |                               | Verpakking                                |        |
|----------------------------|-------------------------------|-------------------------------------------|--------|
| MAC-adrestabel *           | 8000 entries                  | Gebruikershandleiding                     | ✓      |
| Jumbo Frames ondersteuning | ✓                             | Breedte verpakking                        | 302 mm |
| Jumbo frames               | 9000                          | Diepte verpakking                         | 227 mm |
| Packet buffergeheugen      | 0,525 MB                      | Hoogte verpakking                         | 64 mm  |
| Beveiliging                |                               | Gewicht verpakking                        | 1,1 kg |
| IGMP snooping              | ✓                             | Logistieke gegevens                       |        |
| MAC adres filtering        | ✓                             | Code geharmoniseerd systeem (HS) 85176990 |        |
| SSH/SSL support            | ✓                             |                                           |        |
| Multicast-functies         |                               |                                           |        |
| Multicast-ondersteuning    | ✓                             |                                           |        |
| Protocollen                |                               |                                           |        |
| Beheerprotocollen          | SNMP v1,v2,v3, RMON (1,2,3,9) |                                           |        |



4718937621897

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAY-2023. Prints or copies of Information are only valid on the printed Publication date