



TP-Link EAP215-Bridge KIT 867 Mbit/s Wit Power over Ethernet (PoE)

Merk : TP-Link

Artikelcode: EAP215-BRIDGE KIT

Productnaam : EAP215-Bridge KIT

TP-Link EAP215-Bridge KIT. Maximale overdrachtssnelheid van gegevens: 867 Mbit/s, Maximale overdrachtssnelheid van gegevens (5 GHz): 867 Mbit/s, Ethernet LAN, data-overdrachtssnelheden: 10,100,1000 Mbit/s. Ondersteunde beveiligingsalgoritmen: SNMP, SNMPv2, SNMPv3, SSH. Type Power over Ethernet (PoE) ondersteunt: Passive PoE, DC voltage bereik: 12 V. Plaatsing: Paal, Kleur van het product: Wit, Certificering: CE, FCC, RoHS. Soort antenne: Intern, Type antennerichting: Directioneel, Antennefuncties: Ingebouwde antenne



Kenmerken		Poorten & interfaces	
2,4 GHz *	✗	Aantal Ethernet LAN (RJ-45)-poorten *	3
5 GHz *	✓		
6 GHz *	✗		
Maximale overdrachtssnelheid van gegevens *	867 Mbit/s		
Maximale overdrachtssnelheid van gegevens (5 GHz)	867 Mbit/s		
Ethernet LAN, data-overdrachtssnelheden	10,100,1000 Mbit/s		
Netwerkstandaard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n		
Bekabelingstechnologie	10/100/1000Base-T(X)		
MIMO	✓		
MIMO-type	Multi User MIMO		
VLAN=ondersteuning	✓		
Rate limiting	✓		
Quality of Service (QoS)	✓		
BeamForming	✓		
Zendvermogen (CE)	<23dBm (5 GHz, band 1/2, EIRP); <30dBm (5 GHz band3, EIRP)		
Zendvermogen (FCC)	<22dBm (5 GHz band1/4)		
Beveiliging		Energie	
Ondersteunde beveiligingsalgoritmen *	SNMP, SNMPv2, SNMPv3, SSH	Power over Ethernet (PoE) *	✓
MAC adres filtering	✓	Type Power over Ethernet (PoE) ondersteunt	Passive PoE
Remote Authentication Dial-In User Service (RADIUS)	✓	DC voltage bereik	12 V
Access Control List (ACL)	✓		
Beheerfuncties		Design	
Web-gebaseerd management	✓	Plaatsing *	Paal
Syslog	✓	Kleur van het product *	Wit
		Reset button	✓
		LED-indicatoren	✓
		Certificering	CE, FCC, RoHS
		Antenne	
		Soort antenne *	Intern
		Type antennerichting	Directioneel
		Antennefuncties	Ingebouwde antenne
		Antenne versterkingsniveau (max)	11 dBi
		Polarisatie	Dubbele polarisatie
		Gewicht en omvang	
		Breedte	224 mm
		Diepte	79 mm
		Hoogte	60 mm
		Gewicht	330,9 g
		Inhoud van de verpakking	
		Snelstartgids	✓
		Eisen aan de omgeving	
		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
		Bedrijfstemperatuur (T-T)	-40 - 70 °C
		Temperatuur bij opslag	-40 - 70 °C

Eisen aan de omgeving

Luchtvochtigheid bij opslag

5 - 90 procent



4895252502565



0840030709159



840030709159

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.