

DÄTWYLER Cat.5e (Class D) S/UTP patch cable, CU 5502 flex LSOH, AMP v2, grey, 3 m

Product No.	21.05.7803
Manufacturer	SECOMP
Manufacturer No.	21.05.7803
EAN (single piece)	7611990757961

SECOMP®



Cat.5e
Class D

S/UTP

LSOH

DÄTWYLER data cable CU 5502 flex LSOH, assembled on both sides with AMP v2 connectors for use in Fast Ethernet networks, Cat.5e. Halogen-free, flame-retardant, low-smoke.

- Shielded DÄTWYLER cable assembled on both sides with AMP RJ-45 connector, 2nd generation (v2)
- Protective tab for locking pin
- Pin assignment: 8 wires 1 : 1
- Construction: Cable type S/UTP (braided shield)
- Impedance: 100 ohms
- Inner conductor: 8 wires AWG 26 tinned copper stranded wire
- Outer diameter 5.1 mm (approximate)
- Overall shielding: braided shield
- Halogen-free, flame-retardant, low-smoke

Construction:

- Cable type: S/UTP braided shield
- Impedance: 100 ohms
- Inner conductor: 8 wires, AWG 26 copper stranded wire
- Outer diameter: 5.1 mm (approximate)
- Connector: AMP EMT

Technical specifications	
Manufacturer	SECOMP
Product group	Twisted Pair Cable
Product type	S/UTP patch cord
Colour	grey
Length	3 m
Shield type	S/UTP
Transfer quality	Cat5e / Class D
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Bend radius	20 mm
Assignment	EIA/TIA 568A
Locking lever	yes
Colour (Spout)	transparent
External cable diameter	5.1 mm
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	AMP v2
Height of packaging (single piece)	40 mm
Width of packaging (single piece)	220 mm

Depth of packaging (single piece)	240 mm
Package weight (single piece)	0.108 kg