

# DÄTWYLER Cat.5e (Class D) S/UTP patch cable, CU 5502 flex LSOH, AMP v2, grey, 5 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 21.05.7805    |
| <b>Manufacturer</b>       | SECOMP        |
| <b>Manufacturer No.</b>   | 21.05.7805    |
| <b>EAN (single piece)</b> | 7611990757985 |

**SECOMP®**



**Cat.5e**  
Class D

**S/UTP**

**LSOH**

**DÄTWYLER data cable CU 5502 flex LSOH, assembled on both sides with AMP v2 connectors for use in Fast Ethernet networks, Cat.5e. Halogen-free, flame-retardant, low-smoke.**

- Shielded DÄTWYLER cable assembled on both sides with AMP RJ-45 connector, 2nd generation (v2)
- Protective tab for locking pin
- Pin assignment: 8 wires 1 : 1
- Construction: Cable type S/UTP (braided shield)
- Impedance: 100 ohms
- Inner conductor: 8 wires AWG 26 tinned copper stranded wire
- Outer diameter 5.1 mm (approximate)
- Overall shielding: braided shield
- Halogen-free, flame-retardant, low-smoke

## Construction:

- Cable type: S/UTP braided shield
- Impedance: 100 ohms
- Inner conductor: 8 wires, AWG 26 copper stranded wire
- Outer diameter: 5.1 mm (approximate)
- Connector: AMP EMT

| Technical specifications           |                    |
|------------------------------------|--------------------|
| Manufacturer                       | SECOMP             |
| Product group                      | Twisted Pair Cable |
| Product type                       | S/UTP patch cord   |
| Colour                             | grey               |
| Length                             | 5 m                |
| Shield type                        | S/UTP              |
| Transfer quality                   | Cat5e / Class D    |
| Impedance                          | 100 Ohm            |
| Quantity of wires                  | 8                  |
| Conductor cross section (AWG)      | AWG 26             |
| Conductor type                     | Stranded           |
| Crossed                            | no                 |
| Bend radius                        | 20 mm              |
| Assignment                         | EIA/TIA 568A       |
| Locking lever                      | yes                |
| Colour (Spout)                     | transparent        |
| External cable diameter            | 5.1 mm             |
| Cable LSOH                         | yes                |
| Side 1 Connector Type              | RJ-45              |
| Side 1 Connector Gender            | Male               |
| Side 2 Connector Type              | RJ-45              |
| Side 2 Connector Gender            | Male               |
| Connector Type RJ45                | AMP v2             |
| Height of packaging (single piece) | 40 mm              |
| Width of packaging (single piece)  | 190 mm             |

|                                      |         |
|--------------------------------------|---------|
| Depth of packaging<br>(single piece) | 260 mm  |
| Package weight (single<br>piece)     | 0.18 kg |