

DÄTWYLER Cat.5e (Class D) S/UTP patch cable, CU 5502 flex LSOH, Hirose TM11, red, 20 m

Product No.	21.05.8201	SECOMP®
Manufacturer	SECOMP	
Manufacturer No.	21.05.8201	
EAN (single piece)	7611990752959	



Cat.5e
Class D

S/UTP

LSOH

DÄTWYLER data cable CU 5502 flex LSOH, assembled on both sides with Hirose TM11 connectors for use in Fast Ethernet networks, Cat.5e. Halogen-free, flame-retardant, low-smoke.

- Shielded DÄTWYLER cable assembled on both sides with HiRose RJ-45 TM11 plug and anti-kink sleeve
- Pin assignment 8 wires 1 : 1
- Construction: Cable type S/UTP (no pair shielding; overall shielding: braided shield)
- Impedance: 100 ohms
- Inner conductor: 8 wires AWG 26/7 tinned copper stranded wire
- Outer diameter 5.1 mm (approximate)
- Note: Halogen-free cable

Technical specifications	
Manufacturer	SECOMP
Product group	Twisted Pair Cable
Product type	S/UTP patch cord
Colour	red

Length	20 m
Shield type	S/UTP
Transfer quality	Cat5e / Class D
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Locking lever	no
Anti-kink sleeve	Put-on
Colour (Spout)	red
External cable diameter	5.1 mm
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	HiRose TM11
Height of packaging (single piece)	40 mm
Width of packaging (single piece)	210 mm
Depth of packaging (single piece)	240 mm
Package weight (single piece)	0.686 kg