

KERPEN Cat.6 (Class E) Patch Cable S/F, MegaLine F6-90, HiRose TM21, LSOH, blue, 1.5 m

Product No.	21.08.9224
Manufacturer	SECOMP
Manufacturer No.	21.08.9224
EAN (single piece)	7611990757596

SECOMP®



KERPEN DATACOM MegaLine® F6-90 S/F data cable, terminated at both ends with Hirose TM21 connectors, for use in Gigabit Ethernet networks. Halogen-free, flame-retardant, low-smoke.

- High-quality flexible patch cable with special shielding
- Terminated at both ends with shielded RJ-45 HiRose TM21 Class E connectors
- 8-wire 1:1 pinout in accordance with EIA/TIA
- 8-wire twisted pair copper stranded wire, AWG27
- Overall shielding: tinned copper braiding, with each pair of wires additionally shielded separately
- Outer sheath: flame-retardant, halogen-free polyolefin (FR/LSOH)

Construction:

- Cable type: S/FTP (or PiMF)
- Inner conductor: 8-strand AWG 27/7 copper stranded wire
- Colour code: white/blue, white/orange, white/green, white/brown
- Individual shield: aluminium-laminated polyester film (metal side on the outside)
- Overall shielding: tinned copper braid
- Outer sheath: halogen-free, flame-retardant compound

Technical specifications	
Manufacturer	SECOMP
Product group	Twisted Pair Cable
Product type	S/FTP patch cord (PiMF)
Colour	blue
Length	1.5 m
Shield type	S/FTP (PiMF)
Transfer quality	Cat6 / Class E
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 27
Conductor type	Stranded
Crossed	no
Assignment	EIA/TIA 568B
Locking lever	yes
Anti-kink sleeve	Put-on
Colour (Spout)	blue
External cable diameter	5,7 mm
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	HiRose TM21
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	150 mm

Depth of packaging (single piece)	140 mm
Package weight (single piece)	0.062 kg