


# ROLINE Thunderbolt™ 3 Cable, 20GBit/s, 5A, M/M, black, 2 m

<b>Product No.</b>	11.02.9042
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	11.02.9042
<b>EAN (single piece)</b>	7630049611498



**Thunderbolt 3 cables with the USB Type C connector offer you the currently highest possible data transfer rate of up to 40GBit/s (20GBit/s for 1m and 2m) and full Power Delivery support (PD up to 20V 5A / 100W)! The cables also feature DP mode for particularly high-resolution image and sound transmission of up to 5120x2880 @60Hz (5K).**

- Thunderbolt protocols allow maximum data transfer rates of up to 40GBit/s (20GBit/s for 1m and 2m)
- DP mode for connecting a monitor with USB Type C / Thunderbolt 3 connector, with a maximum resolution of 5120x2880 (5K)
- One of the best applications is to connect your Thunderbolt 3 cable with a Thunderbolt device like a corresponding MacBook and matching USB Type C monitor; If Thunderbolt 3 is supported, the full 5K resolution is possible (4K, 3840x2160 @60Hz with USB 3.1 support) and your device gets powered at the same time
- Supports USB Power Delivery up to 20V 5A / 100W, for powering your Macbook, Ultrabook or notebook/laptop
- High-quality cable with improved shielding
- With reversible USB type C connector at both ends
- Gold plated contacts for low wear at high mating cycles
- Colour: black

Thunderbolt and the Thunderbolt logo are trademarks of Intel Corporation in the U.S. and/or other countries.

Technical specifications	
Manufacturer	ROLINE
Product group	Cable
Product type	Thunderbolt™ 3 Cable
Colour	black
Length	2 m
Transfer quality	Thunderbolt™ 3 - 20 Gbit/s
Connection ports	USB Type C (USB-C) Male / USB Type C (USB-C) Male
Side 1 Connector Type	USB Type C (USB-C)
Side 1 Connector Gender	Male
Side 2 Connector Type	USB Type C (USB-C)
Side 2 Connector Gender	Male
Colour (Cable)	black
Maximum data transfer rate	20 Gbit/s
Area of application	External
Supported charging technology	USB-PD - USB Power Delivery
Power (max.)	100 W
Cable shielding	Screened
Hand locking screws	no
Weight	86 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	140 mm
Depth of packaging (single piece)	160 mm
Package weight (single piece)	0.092 kg