

# ROLINE Internal SATA 6.0 Gbit/s Cable, angled, with Latch, 1 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 11.03.1565    |
| <b>Manufacturer</b>       | ROLINE        |
| <b>Manufacturer No.</b>   | 11.03.1565    |
| <b>EAN (single piece)</b> | 7611990195237 |



Utilizing the SATA III specification and with its unique locking latch, you can rest assured your system is safe and secure.

- Connect your high-speed Serial ATA device (e. g. HDD) to a Serial ATA Controller
- Support data transfer rates of up to 6.0 Gbit/s
- Compatible with SATA 1.5 Gbit/s (SATA I) and 3.0 Gbit/s (SATA II)
- Cable with latch on both connectors
- Cable with connector angled to one side, with pull for easy removal
- Narrow cable design to increase internal air flow
- 4-pin cable with ground wires
- Connectors: 2x internal 7-pin SATA

## Technical specifications

|                  |   |
|------------------|---|
| Manufacturer     | ROLINE  |
| Product group    | Cable   |
| Product type     | SATA Cables                                     |
| Colour           | red   |
| Length           | 1 m   |
| Connection ports | SATA 7-pin (Data) Male / SATA 7-pin (Data) Male |
| side 1 connector | SATA 7 pin Male                                 |
| side 2 connector | SATA 7 pin Male, angled                         |

|                       |                   |
|-----------------------|-------------------|
| Side 1 Connector Type | SATA 7-pin (Data) |
|-----------------------|-------------------|

|                         |      |
|-------------------------|------|
| Side 1 Connector Gender | Male |
|-------------------------|------|

|                       |                   |
|-----------------------|-------------------|
| Side 2 Connector Type | SATA 7-pin (Data) |
|-----------------------|-------------------|

|                         |      |
|-------------------------|------|
| Side 2 Connector Gender | Male |
|-------------------------|------|

|              |     |
|--------------|-----|
| Ribbon cable | yes |
|--------------|-----|

|                     |          |
|---------------------|----------|
| Area of application | Internal |
|---------------------|----------|

|                 |              |
|-----------------|--------------|
| Cable shielding | Not screened |
|-----------------|--------------|

|                   |      |
|-------------------|------|
| Cable composition | SATA |
|-------------------|------|

|                         |                              |
|-------------------------|------------------------------|
| Technical particularity | with Latch on the connectors |
|-------------------------|------------------------------|

|        |        |
|--------|--------|
| Weight | 30.6 g |
|--------|--------|

|                                    |       |
|------------------------------------|-------|
| Height of packaging (single piece) | 40 mm |
|------------------------------------|-------|

|                                   |       |
|-----------------------------------|-------|
| Width of packaging (single piece) | 90 mm |
|-----------------------------------|-------|

|                                   |        |
|-----------------------------------|--------|
| Depth of packaging (single piece) | 110 mm |
|-----------------------------------|--------|

|                               |          |
|-------------------------------|----------|
| Package weight (single piece) | 0.031 kg |
|-------------------------------|----------|