## ROLINE 19" PDU for Cabinets 8x 3600W, IEC320 C13 - German Type M, Aluminium, 2 m

**Product No.** 19.07.1628

ROLINE

Manufacturer No. 19.07.1628

**EAN (single piece)** 7630049610903





Manufacturer









19" socket strip with 8x C13 connection and German Type supply cable, 1U, for installation in 19" cabinets, incl. mounting bracket.

- 19 "socket (1UH) for installation in 19" cabinets, incl. installation angles
- Arrangement of sockets: 90°
- Profile of anodized aluminium
- Cable type: 2.0m H05VV-F 3G 1mm<sup>2</sup>, black
- Max load/power: 16A 3600W
- Color: ALU / light gray RAL 7035
- Width: 440mm

| Technical specifications |                 |  |
|--------------------------|-----------------|--|
| Manufacturer             | ROLINE          |  |
| Product group            | Power Bars      |  |
| Product type             | 19" power strip |  |
| Colour                   | Aluminium       |  |
| Length                   | 2 m             |  |

| Function                           | 19" PDU for Cabinets  |
|------------------------------------|---|
| Mounting form                      | 19" Rackmount   |
| Max. capacitance                   | 3600W   |
| Max. voltage                       | 250V AC   |
| ON/OFF Switch                      | no  |
| Number of socket pots              | 8   |
| Quantity of outputs/angles         | 8 / 90°   |
| Output alignment                   | Line  |
| Socket type                        | IEC320 C13, 10A<br>IEC320 C13, 10A                                |
| Material (casing)                  | Aluminium   |
| Colour (Design profile)            | Aluminium   |
| Connection cable                   | H05VV-F 3G 1.5mm <sup>2</sup>                                     |
| Connector plug                     | German Type IEC320  |
| Plug type                          | 3P. German, CEE 7/7, Type-E/F                                     |
| Regional use                       | Germany, Austria, Netherlands<br>France, Czech Republic, Slovakia |
| Height                             | 44 mm   |
| Width                              | 440 mm  |
| Depth                              | 44 mm   |
| Weight                             | 783.3 g   |
| Height of packaging (single piece) | 50 mm   |
| Width of packaging (single piece)  | 110 mm  |
| Depth of packaging (single piece)  | 500 mm  |
| Package weight (single piece)      | 0.892 kg  |
|                                    |   |