ROLINE 19" Automatic Transfer Switch, 2x C20 to 6x C13/2x C19, 16A

Product No. 19.07.3415

ROLINE

Manufacturer ROLIN

Manufacturer No. 19.07.3415

EAN (single piece) 7630049629134







The Automatic Transfer Switch (ATS) is a high availability device designed for providing redundant power for sensitive electronic equipment. Powered by two independent power sources, it makes a rapid switch from one source to the other automatically, when the power supply used to power its connected load fails.

- The ATS Automatic Transfer Switch has two main supplies that provide redundant power to connected IT equipment
- Designed to supply power from the primary source "A". If this source is unavailable for any reason, the device will automatically switch to the secondary source "B", with no interruption to the connected equipment
- Once the primary source "A" is available again, it will automatically switch back, again without interruption to the equipment
- Robust steel construction
- 2x C20 16A inlets
- 2x C19 16A outlets
- 6x C13 10A unswitched sockets
- 19" horizontal rack mounting 1U (44.4mm) high
- 16A max. rated. 220 240VAC 50Hz

| Technical specifications | |
|--------------------------|-----------------|
| Manufacturer | ROLINE |
| Product group | UPS Accessories |

| Product type | Automatic Transfer Switch (ATS) |
|------------------------------------|---|
| Colour | black |
| Scope of delivery | User manual, 2x Input cables: C19-C20, 2x Input cable lockers, SNMP card, accessories for rack installation |
| Dimensions (HxWxD) | 44 x 482.6 x 220 mm |
| Mounting form | 19" Rackmount |
| Technical particularity | Supports SNMP Version3 |
| Operating temperature min. | 0 °C |
| Operating temperature max. | 45 °C |
| Height | 44 mm |
| Width | 482.6 mm |
| Depth | 220 mm |
| Weight | 3079.7 g |
| Height of packaging (single piece) | 140 mm |
| Width of packaging (single piece) | 440 mm |
| Depth of packaging (single piece) | 550 mm |
| Package weight (single piece) | 5.4 kg |
| | |