


# ROLINE Portable EV Charging Cable, Italian Plug - Type 2, Mode 2, 10 A, 2.3 kW, 7.5 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 19.08.0127    |
| <b>Manufacturer</b>       | ROLINE        |
| <b>Manufacturer No.</b>   | 19.08.0127    |
| <b>EAN (single piece)</b> | 7630049633612 |



## ROLINE Portable Charging Cable Mode 2 with Italian Plug (Type L) and Type 2 Connector for Electric and Hybrid Cars - with up to 2.3 kW.

- Enables easy and fast charging at home or on the go
- Suitable for charging electric and hybrid vehicles
- Connections: Type L /(Italian Plug) and Type 2 Connector
- For all electric or hybrid cars with Type 2 connection
- Ergonomically shaped plug and coupler
- IP-Protection of Type 2 Connector: IP65 (mated) / IP54 (unmated)
- IP-Protection of IC-CPD (In-cable control and protection device): IP67
- 10 A / 1-phase (250 VAC)
- Max. Charging Power: 2,3 kW
- Flame retardant (IEC 60332-1)
- Halogen free (IEC 60754-1/2)

### Note:

It is recommended to wire the supply line to the socket with 2.5 mm<sup>2</sup>. Mode 2 emergency charging cable chargers are not suitable for permanently charging an electric car.

| Technical specifications         |                                           |
|----------------------------------|-------------------------------------------|
| Manufacturer                     | ROLINE                                    |
| Product group                    | Power Cables                              |
| Product type                     | Electric car charging cable               |
| Colour                           | black                                     |
| Length                           | 7.5 m                                     |
| Scope of delivery                | Charging Cable, Carrying Bag, User Manual |
| Charging power                   | 2.3 kW                                    |
| Current                          | 10 A                                      |
| Number of phases                 | 1-phase                                   |
| Supported charging technology    | Mode-2                                    |
| Side 1 Connector Type            | CEI23-50, Type-L                          |
| Side 1 Connector Gender          | Male                                      |
| Side 2 Connector Type            | IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)    |
| Side 2 Connector Gender          | Female                                    |
| Material (external cable mantle) | TPU                                       |
| Cable LSOH                       | flame retardant                           |
| Protection class (IP Code)       | IP67<br>IP65<br>IP54                      |
| Technical particularity          | Rated Current: 6/8/10A                    |
| Regional use                     | Italy, San Marino, Vatican City, Albania  |
| Mains connection                 | Power plug Italy, Type-L                  |
| Operating temperature min.       | -30 °C                                    |
| Operating temperature max.       | 50 °C                                     |

|                                    |          |
|------------------------------------|----------|
| Storage temperature min.           | -40 °C   |
| Storage temperature max.           | 85 °C    |
| Height                             | 80 mm    |
| Width                              | 360 mm   |
| Depth                              | 360 mm   |
| Weight                             | 2.875 kg |
| Height of packaging (single piece) | 100 mm   |
| Width of packaging (single piece)  | 340 mm   |
| Depth of packaging (single piece)  | 340 mm   |
| Package weight (single piece)      | 2.5 kg   |