## ROLINE Power Cord 3P German Connector, IEC320 - C19 16A, black, 2 m

Product No. 19.08.1552

Manufacturer ROLINE

Manufacturer No. 19.08.1552

7611990197187



**EAN** (single piece)



## Cable often used for UPS from 3000 VA and for connecting Blade servers.

• Connection cable 16 A with IEC320 C19 Female and 3P German connector plug, angled

• Cable: H05VV-F 3G1.5 3x 1.5mm<sup>2</sup>

• Nominal data: 250 VAC/16 A

• Colour: black

| Technical specifications |   |  |
|--------------------------|---|--|
| Manufacturer             | ROLINE  |  |
| Product group            | Power Cables  |  |
| Product type             | Connection cable  |  |
| Colour                   | black   |  |
| Length                   | 2 m   |  |
| Connection ports         | 3P. German, CEE 7/7, Type-E/F Male / IEC320 C19, 16A Female |  |
| Max. current             | 16 A  |  |
| Max. voltage             | 250V  |  |

| Max. power                              | 3600W   |
|---|---|
| Cable material                          | H05VV-F   |
| Conductor cross section (mm²)           | 1,5mm²  |
| Quantity of wires                       | 3   |
| Side 1 description                      | German Type   |
| Side 1 Connection type                  | 3P German Connector   |
| Side 1 connector external diameter (mm) | 40 mm   |
| Side 2 description                      | Kaltgeräte  |
| Side 2 Connection type                  | IEC320 C19  |
| Side 2 connector external diameter (mm) | 20 x 28 mm  |
| Side 1 Connector Type                   | 3P. German, CEE 7/7, Type-E/F                                     |
| Side 1 Connector<br>Gender              | Male  |
| Side 2 Connector Type                   | IEC320 C19, 16A   |
| Side 2 Connector<br>Gender              | Female  |
| Regional use                            | Germany, Austria, Netherlands<br>France, Czech Republic, Slovakia |
| Weight                                  | 317.1 g   |
| Height of packaging (single piece)      | 50 mm   |
| Width of packaging (single piece)       | 110 mm  |
| Depth of packaging (single piece)       | 250 mm  |
| Package weight (single piece)           | 0.3 kg  |
|   |   |