

ROLINE LineSecure1000

Product No.	19.40.1110
Manufacturer	ROLINE
Manufacturer No.	19.40.1110
EAN (single piece)	7611990154944



LineSecure UPS's work with the "buck & boost" line interactive technology; used when reliable protection against strong voltage fluctuations is essential. Protect against: power failure, power sag, power surge, under voltage, over voltage.

Product features:

- Compact, quiet, user-friendly
 - Desktop and 19" RM models
 - Short circuit and overload protection
 - AVR (Automatic Voltage Regulation)
 - ABM (Automatic Battery Management) increases battery life up to 50%
 - Telephone/Modem connections
 - Shutdown software including License for 1 server
 - Serial Port for advanced Power Management Software (incl. in content of delivery)
 - UPS Management Software : Windows NT/ 2k / XP / 7 / 8 /Server 2003 / 2008 / 2012 x86/x64,
MAC OS X (Intel) 10.6.x, 10.7.x, 10.8.x Mountain Lion, 10.9.x MavericksMAC OS, LINUX
- Content: UPS, Cable set, Software CD

Technical specifications

Manufacturer	ROLINE
Product group	UPS
Product type	UPS Line Interactive

Colour	grey
Scope of delivery	UPS, Software, Cable Set
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive
Power class	1000 ... 1900 VA
Output (VA/W)	1000 / 700
Efficiency	95 %
Backup time	3 min
Backup time full/half-load	3 / 6 min
Dimensions (HxWxD)	210 x 140 x 436 mm
Mounting form	Tower
Voltage (input)	230 V +- 15%
Voltage (output)	230 V
Frequency	50 Hz
Connector type (input)	cold connector IEC320 C14
Outputs	4
Connector type (output)	4x cold connector IEC320 C13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Delay expansion unit	--
Slots for adapter card	0
Slot for adapter card	--
Interface	RS232
RS-232 Interface	Yes
Hot swap batteries	No
Bypass	No

Additional over current protector	Telephone/Fax
-----------------------------------	---------------

Activity	LED
----------	-----

Activity LED	6 LED
--------------	-------

Activity Display	--
------------------	----

incl.Management Software	Windows
--------------------------	---------

Internal cooling	Active, fan
------------------	-------------

Ambient temperature	0-40°C
---------------------	--------

Operating temperature min.	0 °C
----------------------------	------

Operating temperature max.	40 °C
----------------------------	-------

Height	210 mm
--------	--------

Width	140 mm
-------	--------

Depth	436 mm
-------	--------

Weight	15 kg
--------	-------

Height of packaging (single piece)	330 mm
------------------------------------	--------

Width of packaging (single piece)	260 mm
-----------------------------------	--------

Depth of packaging (single piece)	570 mm
-----------------------------------	--------

Package weight (single piece)	15.485 kg
-------------------------------	-----------