

ROLINE LineSecure II 1500

Product No.	19.40.1117
Manufacturer	ROLINE
Manufacturer No.	19.40.1117
EAN (single piece)	7611990979738



LineSecure UPS's work with the "buck & boost" line interactive technology; used when reliable protection against strong voltage fluctuations is essential. Protect against: power failure, power sag, power surge, under voltage, over voltage.

Product features:

- Compact, quiet, user friendly
- Desktop and 19" RM models
- Short circuit and overload protection
- AVR (Automatic Voltage Regulation)
- ABM (Automatic Battery Management) increases battery life up to 50%
- Telephone/Modem connections
- Shutdown software including License for 1 server
- Serial Port for advanced Power Management Software (incl, in content of delivery)
- UPS Management Software : Windows NT/ 2k / XP / 7 / 8 /Server 2003 / 2008 / 2012 x86/x64,
MAC OS X (Intel) 10.6.x, 10.7.x, 10.8.x Mountain Lion, 10.9.x MavericksMAC OS, LINUX
- Content: UPS, Cable set, Software CD

Technical specifications

Manufacturer	ROLINE
Product group	UPS
Product type	UPS Line Interactive

Colour	black
Scope of delivery	UPS, cable set, software CD
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive
Power class	1000 ... 1900 VA
Output (VA/W)	1500 / 960
Efficiency	95 %
Backup time	3 min
Backup time full/half-load	3 / 6 min
Dimensions (HxWxD)	226 x 170 x 450 mm
Mounting form	Tower
Voltage (input)	230V +- 15%
Voltage (output)	230V
Frequency	50Hz
Connector type (input)	cold connector IEC320 C14
Outputs	6
Connector type (output)	6 x connector IEC320 C13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Slots for adapter card	0
Acoustic level	40dBA
Interface	USB, RS232
RS-232 Interface	Yes
USB 2.0 Interface	Yes
Hot swap batteries	No
Bypass	No

Additional over current protector	Telephone/Fax
-----------------------------------	---------------

Activity	Display
----------	---------

Activity LED	--
--------------	----

Activity Display	LCD
------------------	-----

incl.Management Software	Windows
--------------------------	---------

Internal cooling	Active, fan
------------------	-------------

Ambient temperature	0-40°C
---------------------	--------

Operating temperature min.	0 °C
----------------------------	------

Operating temperature max.	40 °C
----------------------------	-------

Height	226 mm
--------	--------

Width	170 mm
-------	--------

Depth	450 mm
-------	--------

Weight	6.9 kg
--------	--------

Height of packaging (single piece)	340 mm
------------------------------------	--------

Width of packaging (single piece)	300 mm
-----------------------------------	--------

Depth of packaging (single piece)	550 mm
-----------------------------------	--------

Package weight (single piece)	25 kg
-------------------------------	-------