ROLINE 10/100Base-TX to 100Base-FX Media Converter

Product No. 21.13.1132

rollne

Manufacturer ROLINE

Manufacturer No. 21.13.1132

EAN (single piece) 7630049628915



This converter changes a Fast Ethernet TP port (RJ45) to multimode fiber optic (SC).

- Supports full wire speed copper-to-fiber media conversion for 10/100Mbit/s speed and media types
- Supports auto-negotiation 10/100Mbps on the copper port
- Auto MDI/MDI-X crossover function on the copper port
- Supports IEEE 802.3x flow control
- Transparent conversion to 802.1Q VLAN tagged packets
- Provides Far End Fault function on FX (fiber) port
- Low power consumption
- Supports DIN rail mounting and wall mounting
- LEDs: Power status, TP speed, TP Link/Activity, FX Link/Activity
- Packet Size: Up to 1536 bytes

• Operating temperature.: 0 °C - +50 °C

• Storage Temperature: -30°C ~ 80°C

Relative Humidity: 5% ~ 95% non-condensing

DC Input via external power adapter

Technical specifications

Manufacturer ROLINE

Product group	Network converters
Product type	Media Converter
Colour	black
Scope of delivery	Media Converter, Power supply unit, USB power cable, Installation manual
RJ-45 Port (Mbps/s)	100
Fibre Ports (Mbps)	100
Quantity of RJ45 ports	1
Quantity of fibre SC ports	1
Converts to	RJ-45/SC
Fibre	Multi mode
Ethernet fibre standard	100Base-FX
Operating temperature min.	0 °C
Operating temperature max.	50 °C
Storage temperature min.	-30 °C
Storage temperature max.	80 °C
Height	59 mm
Width	64 mm
Depth	21 mm
Weight	150 g
Height of packaging (single piece)	60 mm
Width of packaging (single piece)	150 mm
Depth of packaging (single piece)	150 mm

Package weight (single 0.3 kg piece)