


ROLINE Industrial Managed Media Converter Gigabit Ethernet with PoE++ PSE Support

Product No.	21.13.1135	
Manufacturer	ROLINE	
Manufacturer No.	21.13.1135	
EAN (single piece)	7630049621541	



- Industrial Media Converter with PoE++ PSE for general applications
- Tri-speed 10/100M/1Gbps copper to dual-speed 100M/1Gbps fiber conversion
- Comply with IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.3af, 802.3at, 802.3bt standard
- Support full wire speed conversion for Gigabit copper to Gigabit fiber
- Provide dual-speed SFP on fiber port for mounting variety of fiber options
- Provide important LFPT (Link Fault Pass Through) media converter function
- Support Jumbo frame conversion
- Energy Efficient Ethernet (EEE) support
- Alarm events relay output
- Optical Power Alarm (OPA) function
- Auto Laser Shutdown (ALS) function
- Fiber support for multimode, short reach up to long reach single mode fiber, Bi-Di applications
- Web-based configuration management support
- Support SNMP management
- Provide variety of PoE options for different power level applications
- PoE shutdown protection for non-compliant PD, disconnection, over-current and short-circuit

Technical specifications	
Manufacturer	ROLINE
Product group	Network converters
Product type	Media Converter

Colour	black
RJ-45 Port (Mbps/s)	1000
Fibre Ports (Mbps)	1000
Quantity of RJ45 ports	1
Quantity of fibre LC ports	1
Fibre	Multi mode
Ethernet fibre standard	1000Base-SX
Max. range 50 µm fibre	500 m
Max. range 62,5 µm fibre	220 m
Managed	no
Operating temperature min.	-20 °C
Operating temperature max.	70 °C
Height	40 mm
Width	106 mm
Depth	140 mm
Weight	474.8 g
Height of packaging (single piece)	50 mm
Width of packaging (single piece)	150 mm
Depth of packaging (single piece)	200 mm
Package weight (single piece)	0.6 kg