## ROLINE Industrial Switch, 7x RJ-45, 1x ST, unmanaged

Product No. Manufacturer Manufacturer No. EAN (single piece) 21.13.1151 ROLINE 21.13.1151 7611990176694





- Fast Ethernet switch with 7x 10/100Base-T ports and 1x 100Base-FX port
- Wide operating temperature range for temperature critical environment
- Support DIN rail mounting
- Industrial-rated Emission and Immunity performance
- Provides wire speed store-and-forward switching
- Supports IEEE 802.3x flow control for full-duplex operation
- Supports Back-pressure flow control for half-duplex operation
- Power: Input: 7 30V DC, Consumption: 6.5W (max.)
- DC Input via terminal block or DC power jack (6.3mm/2.0mm)
- Operating Temperature: 20 °C +70 °C
- As Power Supply Unit we recommend 21.13.1226

| Technical specifications |                      |  |
|--------------------------|----------------------|--|
| Manufacturer             | ROLINE               |  |
| Product group            | Network Switches     |  |
| Product type             | Fast Ethernet Switch |  |
| Colour                   | black                |  |
| Network standard         | Fast Ethernet        |  |
| LAN (Mbps)               | 10/100               |  |
| Quantity of ports        | 8                    |  |

| Fast Ethernet Ports RJ-<br>45            | 7                             |
|--|-------------------------------|
| Fast Ethernet Ports Fibre                | 1                             |
| Mounting form                            | DIN Rail                      |
| Management                               | no                            |
| Stackable                                | no                            |
| Dimensions (HxWxD)                       | 106 x 40 x 140 mm             |
| Power supply unit<br>(internal/external) | External                      |
| Mains connection                         | Loose cable / screw terminals |
| Operating temperature min.               | -20 °C                        |
| Operating temperature max.               | 70 °C                         |
| Height                                   | 106 mm                        |
| Width                                    | 40 mm                         |
| Depth                                    | 140 mm                        |
| Weight                                   | 0.64 kg                       |
| Height of packaging<br>(single piece)    | 70 mm                         |
| Width of packaging<br>(single piece)     | 150 mm                        |
| Depth of packaging<br>(single piece)     | 210 mm                        |
| Package weight (single<br>piece)         | 0.637 kg                      |