ROLINE S/FTP Cable Cat.7, with RJ-45 connectors (500 MHz / Class EA), LSOH, grey, 3 m

Product No. 21.15.0853


ROLINE

Manufacturer No. 21.15.0853

EAN (single piece) 7611990110735



Manufacturer











The right solution for a network connection with data transfer rate up to 10 Gbit/s, at a frequency of 500 MHz

- Patch cord for networking connections between devices
- Prepared shielded Twisted Pair cable (PiMF) with Shielded RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- Impedance: 100 Ohm
- · Colour: grey
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 8 lines + pairs shielded with aluminium foil, complete shielding in tinned

copper braid

| Technical specifications | | |
|--------------------------|--------------------|--|
| Manufacturer | ROLINE | |
| Product group | Twisted Pair Cable | |
| Product type | S/FTP Patchcord | |
| Colour | grey | |

| Length | 3 m |
|------------------------------------|------------------|
| Shield type | SFTP |
| Transfer quality | Cat6A / Class EA |
| Impedance | 100 Ohm |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 26 |
| Conductor type | Stranded |
| Crossed | no |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | grey |
| Cable LSOH | yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Weight | 121 g |
| Height of packaging (single piece) | 50 mm |
| Width of packaging (single piece) | 170 mm |
| Depth of packaging (single piece) | 190 mm |
| Package weight (single piece) | 0.12 kg |
| | |