

ROLINE UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, white, 1.5 m

| | |
|--------------------|---------------|
| Product No. | 21.15.0984 |
| Manufacturer | ROLINE |
| Manufacturer No. | 21.15.0984 |
| EAN (single piece) | 7630049610620 |



Cat.6A
Class EA

U/UTP

DATA CENTER
Product

LSOH

Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

| Technical specifications | |
|--------------------------|--------------------|
| Manufacturer | ROLINE |
| Product group | Twisted Pair Cable |
| Product type | UTP Patch Cables |
| Colour | white |
| Length | 1.5 m |
| Shield type | UTP |

| | |
|---------------------------------------|------------------|
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 32 |
| Conductor type | Stranded |
| Crossed | no |
| Slim cable | yes |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| External cable diameter | 3.4 +/- 0.2mm |
| Cable LSOH | yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -10 °C |
| Operating temperature max. | 60 °C |
| Weight | 25.5 g |
| Height of packaging (single piece) | 10 mm |
| Width of packaging (single piece) | 120 mm |
| Depth of packaging (single piece) | 150 mm |
| Package weight (single piece) | 0.027 kg |