

# ROLINE U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, white, 5 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 21.15.1705    |
| <b>Manufacturer</b>       | ROLINE        |
| <b>Manufacturer No.</b>   | 21.15.1705    |
| <b>EAN (single piece)</b> | 7630049610712 |



**Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.**

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

## Technical specifications

|               |                    |
|---------------|--------------------|
| Manufacturer  | ROLINE             |
| Product group | Twisted Pair Cable |
| Product type  | FTP Patch Cord     |
| Colour        | white              |
| Length        | 5 m                |
| Shield type   | FTP                |

|                  |                  |
|------------------|------------------|
| Transfer quality | Cat6A / Class EA |
|------------------|------------------|

|                   |   |
|-------------------|---|
| Quantity of wires | 8 |
|-------------------|---|

|                |      |
|----------------|------|
| Conductor type | Wire |
|----------------|------|

|         |    |
|---------|----|
| Crossed | no |
|---------|----|

|            |     |
|------------|-----|
| Slim cable | yes |
|------------|-----|

|                |       |
|----------------|-------|
| Colour (Spout) | white |
|----------------|-------|

|            |     |
|------------|-----|
| Cable LSOH | yes |
|------------|-----|

|                       |       |
|-----------------------|-------|
| Side 1 Connector Type | RJ-45 |
|-----------------------|-------|

|                         |      |
|-------------------------|------|
| Side 1 Connector Gender | Male |
|-------------------------|------|

|                       |       |
|-----------------------|-------|
| Side 2 Connector Type | RJ-45 |
|-----------------------|-------|

|                         |      |
|-------------------------|------|
| Side 2 Connector Gender | Male |
|-------------------------|------|

|                     |          |
|---------------------|----------|
| Connector Type RJ45 | Standard |
|---------------------|----------|

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -10 °C |
|----------------------------|--------|

|                            |       |
|----------------------------|-------|
| Operating temperature max. | 60 °C |
|----------------------------|-------|

|        |        |
|--------|--------|
| Weight | 72.2 g |
|--------|--------|

|                                    |       |
|------------------------------------|-------|
| Height of packaging (single piece) | 10 mm |
|------------------------------------|-------|

|                                   |        |
|-----------------------------------|--------|
| Width of packaging (single piece) | 100 mm |
|-----------------------------------|--------|

|                                   |        |
|-----------------------------------|--------|
| Depth of packaging (single piece) | 100 mm |
|-----------------------------------|--------|

|                               |          |
|-------------------------------|----------|
| Package weight (single piece) | 0.044 kg |
|-------------------------------|----------|