ROLINE U/FTP Data Center Cable Cat.7, with RJ45 Plug, 500 MHz(Class EA), LSOH, slim, white, 2 m

Product No. Manufacturer Manufacturer No. EAN (single piece) 21.15.1712 ROLINE 21.15.1712 7630049610750



Image: Control of the con

Category 7 twisted-pair cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable cable thanks to moulded-on bend protection
- Suitable as a cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

| Technical specifications | | |
|--------------------------|--------------------|--|
| Manufacturer | ROLINE | |
| Product group | Twisted Pair Cable | |
| Product type | FTP Patch Cord | |
| Colour | white | |
| Length | 2 m | |
| Shield type | FTP | |

| Transfer quality | Cat6A / Class EA |
|---------------------------------------|------------------|
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 32 |
| Conductor type | Stranded |
| Crossed | no |
| Slim cable | yes |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Cable LSOH | yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -10 °C |
| Operating temperature max. | 60 °C |
| Weight | 32.7 g |
| Height of packaging (single piece) | 10 mm |
| Width of packaging (single piece) | 100 mm |
| Depth of packaging (single piece) | 100 mm |
| Package weight (single piece) | 0.044 kg |