

# ROLINE UTP Cable Cat.6 Component Level, LSOH, red, 5 m

**Product No.** 21.15.2515  
**Manufacturer** ROLINE  
**Manufacturer No.** 21.15.2515  
**EAN (single piece)** 7611990167814

**roline**  
Designed for Professionals



**Cat.6**  
Class E

**U/UTP**

**LSOH**

**COMPONENT**  
Level Tested

Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Halogen-free, flame retardant, low smoke.

## 100 % Component level testing

| Technical specifications |                    |
|--------------------------|--------------------|
| Manufacturer             | ROLINE             |
| Product group            | Twisted Pair Cable |
| Product type             | UTP Patch Cables   |
| Colour                   | red                |
| Length                   | 5 m                |
| Shield type              | UTP                |
| Transfer quality         | Cat6 / Class E     |

|                                    |          |
|------------------------------------|----------|
| Component-Level certified          | Yes      |
| Impedance                          | 100 Ohm  |
| Quantity of wires                  | 8        |
| Conductor type                     | Wire     |
| Crossed                            | No       |
| Colour (Spout)                     | red      |
| Cable LSOH                         | Yes      |
| Side 1 Connector Type              | RJ-45    |
| Side 1 Connector Gender            | Male     |
| Side 2 Connector Type              | RJ-45    |
| Side 2 Connector Gender            | Male     |
| Connector Type RJ45                | Standard |
| Weight                             | 184.8 g  |
| Height of packaging (single piece) | 20 mm    |
| Width of packaging (single piece)  | 170 mm   |
| Depth of packaging (single piece)  | 210 mm   |
| Package weight (single piece)      | 0.196 kg |