## ROLINE UTP Cable Cat.6 Component Level, LSOH, black, 0.5 m

**Product No.** 21.15.2550


**Manufacturer** ROLINE

**Manufacturer No.** 21.15.2550

**EAN (single piece)** 7611990170357

















Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Halogen-free, flame retardant, low smoke.

## 100 % Component level testing

| Technical specifications |                    |  |
|--------------------------|--------------------|--|
| Manufacturer             | ROLINE             |  |
| Product group            | Twisted Pair Cable |  |
| Product type             | UTP Patch Cables   |  |
| Colour                   | black              |  |
| Length                   | 0.5 m              |  |
| Shield type              | UTP                |  |
| Transfer quality         | Cat6 / Class E     |  |

| Component-Level certified          | yes        |
|------------------------------------|------------|
| Impedance                          | 100 Ohm    |
| Conductor cross section (AWG)      | AWG 24     |
| Conductor type                     | Stranded   |
| Crossed                            | no         |
| Locking lever                      | yes        |
| Anti-kink sleeve                   | Moulded-on |
| Colour (Spout)                     | black      |
| Cable LSOH                         | yes        |
| Side 1 Connector Type              | RJ-45      |
| Side 1 Connector<br>Gender         | Male       |
| Side 2 Connector Type              | RJ-45      |
| Side 2 Connector<br>Gender         | Male       |
| Connector Type RJ45                | Standard   |
| Weight                             | 27 g       |
| Height of packaging (single piece) | 20 mm      |
| Width of packaging (single piece)  | 140 mm     |
| Depth of packaging (single piece)  | 190 mm     |
| Package weight (single piece)      | 0.047 kg   |
|                                    |            |