## ROLINE UTP Cable Cat.6 Component Level, LSOH, black, 1 m

| Product No.        |  |
|--------------------|--|
| Manufacturer       |  |
| Manufacturer No.   |  |
| EAN (single piece) |  |

21.15.2551 ROLINE 21.15.2551 7611990170388





Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Halogen-free, flame retardant, low smoke.

## 100 % Component level testing

| Technical specifications |                    |  |
|--------------------------|--------------------|--|
| Manufacturer             | ROLINE             |  |
| Product group            | Twisted Pair Cable |  |
| Product type             | UTP Patch Cables   |  |
| Colour                   | black              |  |
| Length                   | 1 m                |  |
| Shield type              | UTP                |  |
| Transfer quality         | Cat6 / Class E     |  |

| Component-Level<br>certified          | yes        |
|---------------------------------------|------------|
| Impedance                             | 100 Ohm    |
| Conductor cross section<br>(AWG)      | AWG 24     |
| Conductor type                        | Stranded   |
| Crossed                               | no         |
| Locking lever                         | yes        |
| Anti-kink sleeve                      | Moulded-on |
| Colour (Spout)                        | black      |
| Cable LSOH                            | yes        |
| Side 1 Connector Type                 | RJ-45      |
| Side 1 Connector<br>Gender            | Male       |
| Side 2 Connector Type                 | RJ-45      |
| Side 2 Connector<br>Gender            | Male       |
| Connector Type RJ45                   | Standard   |
| Weight                                | 44.9 g     |
| Height of packaging<br>(single piece) | 20 mm      |
| Width of packaging<br>(single piece)  | 110 mm     |
| Depth of packaging<br>(single piece)  | 200 mm     |
| Package weight (single<br>piece)      | 0.053 kg   |
|                                       |            |