ROLINE UTP Cable Cat.6 Component Level, LSOH, black, 5 m

| Product No. | | | |
|--------------------|--|--|--|
| Manufacturer | | | |
| Manufacturer No. | | | |
| EAN (single piece) | | | |

21.15.2555 ROLINE 21.15.2555 7611990170425



Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Halogen-free, flame retardant, low smoke.

100 % Component level testing

| Technical specifications | | | |
|--------------------------|--------------------|--|--|
| Manufacturer | ROLINE | | |
| Product group | Twisted Pair Cable | | |
| Product type | UTP Patch Cables | | |
| Colour | black | | |
| Length | 5 m | | |
| Shield type | UTP | | |
| Transfer quality | Cat6 / Class E | | |

| Component-Level certified | yes |
|---------------------------------------|------------|
| Impedance | 100 Ohm |
| Conductor cross section (AWG) | AWG 24 |
| Conductor type | Stranded |
| Crossed | no |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | black |
| Cable LSOH | yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Weight | 187.3 g |
| Height of packaging (single piece) | 30 mm |
| Width of packaging (single piece) | 190 mm |
| Depth of packaging (single piece) | 200 mm |
| Package weight (single piece) | 0.09 kg |
| | |