## ROLINE S/FTP Patch Cord Cat.6 Component Level, LSOH, red, 3 m

Product No.	21.15.2613	roline Designed for Professionals
Manufacturer	ROLINE	Designed for Endessioners
Manufacturer No.	21.15.2613	
EAN (single piece)	7611990135004	
	UTP = U/UTP UTP = U/UTP UTP = U/UTP FTP = F/UTP FTP = F/UTP SkFTP (Cat.5e) = SkFTP (Cat.6) = SkFTP (Cat.6) = SkFTP (Cat.6)	

n: aluminium clad foil 7. Red: tinned copper braid



Patch cable for networking connections between devices. Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4pair stranded copper wire. Complete braid shielding. Pairs shielded with aluminium clad polyester foil. Halogen-free, flame retardant, low smoke.

## **100% Component Level testing**

Technical specifications		
Manufacturer	ROLINE	
Product group	Twisted Pair Cable	
Product type	S/FTP Patchcord	
Colour	red	
Length	3 m	
Shield type	SFTP	
Transfer quality	Cat6 / Class E	

Component-Level certified	yes
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	red
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	115 g
Height of packaging (single piece)	40 mm
Width of packaging (single piece)	150 mm
Depth of packaging (single piece)	180 mm
Package weight (single piece)	0.123 kg