

ROLINE UTP Patch Cord Cat.6A, Component Level, LSOH, grey, 10 m

| | |
|--------------------|---------------|
| Product No. | 21.15.2707 |
| Manufacturer | ROLINE |
| Manufacturer No. | 21.15.2707 |
| EAN (single piece) | 7611990137350 |



Cat.6A
Class EA

U/UTP

LSOH

COMPONENT
Level Tested

Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire.

100% Component Level testing

- GHMT Certificate No. z4425b-16-E

| Technical specifications | |
|--------------------------|--------------------|
| Manufacturer | ROLINE |
| Product group | Twisted Pair Cable |
| Product type | UTP Patch Cables |
| Colour | grey |
| Length | 10 m |
| Shield type | UTP |

| | |
|------------------------------------|------------------|
| Transfer quality | Cat6A / Class EA |
| Component-Level certified | yes |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 26 |
| Conductor type | Stranded |
| Crossed | no |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | grey |
| Cable LSOH | yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Weight | 357.4 g |
| Height of packaging (single piece) | 60 mm |
| Width of packaging (single piece) | 170 mm |
| Depth of packaging (single piece) | 200 mm |
| Package weight (single piece) | 0.404 kg |