ROLINE UTP Patch Cord Cat.6A, Component Level, LSOH, yellow, 3 m

Product No.	21.15.2723	roline Dasigned for Professionals
Manufacturer	ROLINE	
Manufacturer No.	21.15.2723	
EAN (single piece)	7611990137572	
	UTP = U/UTP UTP = U/UTP FTP = F/UTP FTP = F/UTP SFTP (Cat.6e) SFTP (Cat.6e) SFTP (Cat.6e) SFTP (Cat.6e) SFTP (PMMF) Green: aluminium clad fuil / Red: timed copper braining	KI



Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire.

100% Component Level testing

Technical specifications		
Manufacturer	ROLINE	
Product group	Twisted Pair Cable	
Product type	UTP Patch Cables	
Colour	yellow	
Length	3 m	
Shield type	UTP	
Transfer quality	Cat6A / Class EA	

Component-Level certified	yes
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	yellow
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	120.14 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	190 mm
Depth of packaging (single piece)	200 mm
Package weight (single piece)	0.15 kg