## ROLINE UTP Patch Cord Cat.6A, Component Level, LSOH, green, 5 m

Product No. Manufacturer Manufacturer No.	21.15.2735 ROLINE 21.15.2735	<b>roline</b> Designed for Professionals
EAN (single piece)	7611990137695	
	UTP = U/UTP UTP = U/UTP UTP = F/UTP S/FTP (Cat.6e) = SF/UTP S/FTP (Cat.6e) = S/FTP (Cat.6) = S/FTP (PiMF)	

en: aluminium clad foil 7. Red: tinned copper braid



Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire.

## **100% Component Level testing**

Technical specifications		
Manufacturer	ROLINE	
Product group	Twisted Pair Cable	
Product type	UTP Patch Cables	
Colour	green	
Length	5 m	
Shield type	UTP	
Transfer quality	Cat6A / Class EA	

Component-Level certified	yes
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	green
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	182 g
Height of packaging (single piece)	40 mm
Width of packaging (single piece)	180 mm
Depth of packaging (single piece)	190 mm
Package weight (single piece)	0.221 kg