ROLINE UTP Patch Cord Cat.6A, Component Level, LSOH, black, 3 m

Product No. Manufacturer Manufacturer No. EAN (single piece)	21.15.2753 ROLINE 21.15.2753 7611990138890	roline Designed for Professionals
	UTP = U/UTP UTP = U/UTP FTP = F/UTP FTP = F/UTP S/FTP (Cat.8e) = S/FTP (Cat.8) = S/FTP (Cat.8) = S/FTP (P/MF)	

n: aluminium clad foil 7 Red: tinned copper braid



Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire.

100% Component Level testing

Technical specifications		
Manufacturer	ROLINE	
Product group	Twisted Pair Cable	
Product type	UTP Patch Cables	
Colour	black	
Length	3 m	
Shield type	UTP	
Transfer quality	Cat6A / Class EA	

Component-Level certified	yes
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	black
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	114.2 g
Height of packaging (single piece)	30 mm
Width of packaging (single piece)	180 mm
Depth of packaging (single piece)	190 mm
Package weight (single piece)	0.192 kg