## ROLINE U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, blue, 3 m

Product No. Manufacturer Manufacturer No. EAN (single piece)	21.15.3346 ROLINE 21.15.3346 7630049622524	<b>roline</b> Designed for Professionals
	UTP = UUTP $UTP = UUTP$ $FTP = FUTP$ $UTP = FUTP$	

aluminium clad foil / Red: tinned copper braid



## Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminiumlaminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- $\ensuremath{\cdot}$  Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

Technical specifications		
Manufacturer	ROLINE	
Product group	Twisted Pair Cable	
Product type	FTP Patch Cord	
Colour	blue	
Length	3 m	
Shield type	FTP	

Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 32
Conductor type	Stranded
Crossed	no
Slim cable	yes
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	blue
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-10 °C
Operating temperature max.	60 °C
Weight	47.3 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm
Package weight (single piece)	0.06 kg