

ROLINE UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, blue, 0.5 m

| | |
|---------------------------|---------------|
| Product No. | 21.15.3942 |
| Manufacturer | ROLINE |
| Manufacturer No. | 21.15.3942 |
| EAN (single piece) | 7630049615168 |



Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

Technical specifications

| | |
|---------------|--------------------|
| Manufacturer | ROLINE |
| Product group | Twisted Pair Cable |
| Product type | UTP Patch Cables |
| Colour | blue |
| Length | 0.5 m |
| Shield type | UTP |

| | |
|------------------|------------------|
| Transfer quality | Cat6A / Class EA |
|------------------|------------------|

| | |
|-------------------|---|
| Quantity of wires | 8 |
|-------------------|---|

| | |
|----------------|------|
| Conductor type | Wire |
|----------------|------|

| | |
|---------|----|
| Crossed | no |
|---------|----|

| | |
|------------|-----|
| Slim cable | yes |
|------------|-----|

| | |
|-------------------------|---------------|
| External cable diameter | 3.4 +/- 0.2mm |
|-------------------------|---------------|

| | |
|------------|-----|
| Cable LSOH | yes |
|------------|-----|

| | |
|-----------------------|-------|
| Side 1 Connector Type | RJ-45 |
|-----------------------|-------|

| | |
|-------------------------|------|
| Side 1 Connector Gender | Male |
|-------------------------|------|

| | |
|-----------------------|-------|
| Side 2 Connector Type | RJ-45 |
|-----------------------|-------|

| | |
|-------------------------|------|
| Side 2 Connector Gender | Male |
|-------------------------|------|

| | |
|---------------------|----------|
| Connector Type RJ45 | Standard |
|---------------------|----------|

| | |
|----------------------------|--------|
| Operating temperature min. | -10 °C |
|----------------------------|--------|

| | |
|----------------------------|-------|
| Operating temperature max. | 60 °C |
|----------------------------|-------|

| | |
|--------|--------|
| Weight | 11.8 g |
|--------|--------|

| | |
|------------------------------------|-------|
| Height of packaging (single piece) | 10 mm |
|------------------------------------|-------|

| | |
|-----------------------------------|--------|
| Width of packaging (single piece) | 150 mm |
|-----------------------------------|--------|

| | |
|-----------------------------------|--------|
| Depth of packaging (single piece) | 130 mm |
|-----------------------------------|--------|

| | |
|-------------------------------|---------|
| Package weight (single piece) | 0.02 kg |
|-------------------------------|---------|