## ROLINE S/FTP Patch Cord Cat.6A / Class EA, LSOH, Slim PoE, grey, 3 m

**Product No.** 21.15.4313


Designed for Professiona

**Manufacturer** ROLINE

**Manufacturer No.** 21.15.4313

**EAN (single piece)** 7630049634046











## S/FTP (PiMF) Cat. 6A LSOH Patch Cord with shielded RJ-45 connectors on both sides. PoE-capable although it is slim, flexible and tangle-free.

- S/FTP (PiMF) LSOH Cat. 6A Patch Cord
- For use in Gigabit Ethernet networks, especially for connecting devices (e.g. IP cameras)
- Slim, flexible and tangle-free
- Suitable for PoE applications and multimedia applications where the extension is working over TP
- High quality plugs with gold plated contacts
- · Durable due to moulded kink protection
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire, complete braid shielding, pairs shielded with aluminium foil

Technical specifications			
Manufacturer	ROLINE		
Product group	Twisted Pair Cable		
Product type	S/FTP Patchcord		

Colour	grey
Length	3 m
Shield type	PiMF
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 28
Conductor type	Stranded
Bend radius	Min. 27 mm
Locking lever	yes
Anti-kink sleeve	Moulded-on
External cable diameter	4.5 +/-0.2mm
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-10 °C
Operating temperature max.	60 °C
Storage temperature min.	-20 °C
Storage temperature max.	75 °C
Weight	115 g
Height of packaging (single piece)	27 mm

Width of packaging (single piece)	20 mm
Depth of packaging (single piece)	30 mm
Package weight (single piece)	0.04 kg