ROLINE Fibre Optic Jumper Cable Duplex, 9/125µm, OS2, LC/LC, APC, Steel Armored, white, 3 m

Product No. Manufacturer Manufacturer No. EAN (single piece) 21.15.8632 ROLINE 21.15.8632 7630049621800









ROLINE LSOH fiber optic patch cable with single mode fibers in OS2 quality.

- Cable sheathing made of halogen-free, low smoke and flame-retardant material
- Assembled with high-quality connectors with ceramic ferrule
- Core structure: Duplex cable I-VH
- High tensile strength due to aramid yarn strain relief
- Steel armored
- Compared to standard fiber optic patch cables, these cables are additionally protected by a flexible steel spiral helix
- Due to this high-quality cable construction, FO cables are tread-resistant and suitable for applications with increased mechanical demands
- Only suitable for indoor use

Technical specifications	
Manufacturer	ROLINE
Product group	Fibre optic cable
Product type	Fibre Optic Jumper Cables OS2
Colour	white

Length	3 m
Quantity of fibre	2
Cable type	Duplex Cable
External cable	no
Fibre section	Single mode 9/125µm OS2
Connection ports	LC APC / LC APC
Side 1 Connector Type	LC APC
Side 2 Connector Type	LC APC
Min. Bending radius, static	30 mm
Min. Bending radius, dynamic	60 mm
Colour (Cable)	white
Aramid strain relief	yes
Cable LSOH	yes
Flame retardant according to IEC 60332- 1-2	yes
Low smoke according to IEC 61034-2	yes
Halogen free according to IEC 60754-2	yes
Armouring	yes
Max. insertion loss	0.3 dB
Min. return loss	60 dB
Weight	86.8 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	150 mm
Depth of packaging (single piece)	150 mm

Package weight (single 0.096 kg piece)