## ROLINE Fibre Optic Jumper Cable, Duplex, 50/125μm, OM4, LC/LC, UNIBOOT, violet, 5 m

**Product No.** 21.15.8654

roline

Manufacturer

**ROLINE** 

Manufacturer No.

21.15.8654

**EAN** (single piece)

7630049634213





ROLINE Fiber Optic Uniboot LSOH Patch Cord LC/LC in OM4 quality for high-performance fiber optic cabling in excellent ROLINE quality. A uniboot patch cord is ideal for a high-density environment. Compared to the conventional duplex connector, the design is more compact and only one cable is used for two lines, which enables usage in a high-density environment. Changing the fiber polarity is easily possible without special tools.

- Fiber Optic Duplex LC/LC Patch Cord with fiber type Multi-Mode 50/125µm, OM4
- Uniboot for high-density environments
- Fiber polarity can be changed easily without special tools
- Assembled with high-quality connectors with ceramic ferrule
- Material and clothing in ROLINE quality
- Cable sheathing is made of halogen-free, low smoke and flame-retardant material

| Technical specifications |                               |  |
|--------------------------|-------------------------------|--|
| Manufacturer             | ROLINE                        |  |
| Product group            | Fibre optic cable             |  |
| Product type             | Fibre Optic Jumper Cables OM4 |  |
| Colour                   | violet                        |  |
| Length                   | 5 m                           |  |
| Quantity of fibre        | 2                             |  |

| Cable type                                 | Duplex Cable                  |
|--|-------------------------------|
| External cable                             | no                            |
| Fibre section                              | Multi mode 50/125µm OM4       |
| Connection ports                           | LC / LC                       |
| Side 1 Connector Type                      | LC                            |
| Side 2 Connector Type                      | LC                            |
| Bend radius                                | Static: 20 mm, Dynamic: 40 mm |
| Min. Bending radius,<br>static             | 20 mm                         |
| Min. Bending radius,<br>dynamic            | 40 mm                         |
| Colour (Cable)                             | violet                        |
| Crossed                                    | yes                           |
| External cable diameter                    | 2 mm                          |
| Mantle of external cable                   | LS0H                          |
| Cable LSOH                                 | yes                           |
| Flame retardant according to IEC 60332-1-2 | yes                           |
| Low smoke according to IEC 61034-2         | yes                           |
| Halogen free according to IEC 60754-2      | yes                           |
| Max. insertion loss                        | 0.3 dB                        |
| Min. return loss                           | 30 dB                         |
| Weight                                     | 35.7 g                        |
| Height of packaging (single piece)         | 10 mm                         |
| Width of packaging (single piece)          | 150 mm                        |
| Depth of packaging (single piece)          | 150 mm                        |
|  |                               |

Package weight (single 0.08 kg piece)