

# ROLINE FO Jumper Cable 50/125µm OM3, LC/LC, Low-Loss-Connector, turquoise, 0.5 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 21.15.8820    |
| <b>Manufacturer</b>       | ROLINE        |
| <b>Manufacturer No.</b>   | 21.15.8820    |
| <b>EAN (single piece)</b> | 7611990119967 |



**LSOH**

## ROLINE Fiber-Patchcable in OM3 quality for a high performance glas cabling

- Security for the future! The OM3 fiber and connector quality with very low insertion loss ensure an excellent quality at very high bandwidths.
- Material and assembly in ROLINE quality
- The cable assembled with "low-loss" connectors achieve very good values for insertion loss and reflection. In comparison:
  - Typical attenuation of a standard LC connector: 0.5 dB
  - Typical attenuation of a low-loss LC connector: 0.15 dB
- Duplex cables with fiber type Multi-mode 50/125µm, OM3
- Color: turquoise

### Technical specifications

|               |                               |
|---------------|-------------------------------|
| Manufacturer  | ROLINE                        |
| Product group | Fibre optic cable             |
| Product type  | Fibre Optic Jumper Cables OM3 |
| Colour        | turquoise                     |
| Length        | 0.5 m                         |

|                                       |                   |
|---------------------------------------|-------------------|
| Quantity of fibre                     | 2                 |
| Conductor composition                 | Compact conductor |
| Cable type                            | Duplex Cable      |
| External cable                        | no                |
| Fibre section                         | 50/125µm OM3      |
| Connection ports                      | LC / LC           |
| Side 1 Connector Type                 | LC                |
| Side 2 Connector Type                 | LC                |
| Aramid strain relief                  | yes               |
| External cable diameter               | 2,8x6 mm          |
| Mantle of external cable              | LS0H              |
| Cable LSOH                            | yes               |
| Weight                                | 8.4 g             |
| Height of packaging<br>(single piece) | 10 mm             |
| Width of packaging<br>(single piece)  | 200 mm            |
| Depth of packaging<br>(single piece)  | 290 mm            |
| Package weight (single<br>piece)      | 0.02 kg           |