ROLINE FO Jumper Cable 50/125µm OM3, LC/LC, Low-Loss-Connector, turquoise, 5 m

Product No. Manufacturer Manufacturer No. EAN (single piece) 21.15.8825 ROLINE 21.15.8825 7611990120017





• Security for the future! The OM3 fiber and connector quality with very low insertion loss ensure an excellent quality at very high bandwidths.

• Material and assembly in ROLINE quality

• The cable assembled with "low-loss" connectors achieve very good values for insertion loss and reflection. In comparison:

- Typical attenuation of a standard LC connector: 0.5 dB
- Typical attenuation of a low-loss LC connector: 0.15 dB
- Duplex cables with fiber type Multi-mode $50/125\mu m$, OM3
- Color: turquoise

Technical specifications		
Manufacturer	ROLINE	
Product group	Fibre optic cable	
Product type	Fibre Optic Jumper Cables OM3	
Colour	turquoise	
Length	5 m	
Quantity of fibre	2	

Conductor composition	Compact conductor
Cable type	Duplex Cable
External cable	no
Fibre section	Multi mode 50/125µm OM3
Connection ports	LC / LC
Side 1 Connector Type	LC
Side 2 Connector Type	LC
Colour (Cable)	turquoise
Aramid strain relief	yes
External cable diameter	2,8x6 mm
Mantle of external cable	LSOH
Cable LSOH	yes
Max. insertion loss	0.15 dB
Operating temperature min.	-20 °C
Operating temperature max.	70 °C
Storage temperature min.	-40 °C
Storage temperature max.	80 °C
Weight	35.4 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	200 mm
Depth of packaging (single piece)	290 mm
Package weight (single piece)	0.06 kg