

# ROLINE FO Jumper Cable 50/125µm OM3, LC/LC, Low-Loss-Connector, turquoise, 10 m

Product No.	21.15.8828
Manufacturer	ROLINE
Manufacturer No.	21.15.8828
EAN (single piece)	7611990120031



**LSOH**

## ROLINE F.O. Patchcable in OM3-Quality for a high performance connection.

- Security for the future! The OM3 fiber and connector quality with very low insertion loss ensure an excellent quality at very high bandwidths.
- Material and assembly in ROLINE quality
- The cable assembled with "low-loss" connectors achieve very good values for insertion loss and reflection. In comparison:
  - Typical attenuation of a standard LC connector: 0.5 dB
  - Typical attenuation of a low-loss LC connector: 0.15 dB
- Duplex cables with fiber type Multi-mode 50/125µm, OM3
- Color: turquoise

Technical specifications	
Manufacturer	ROLINE
Product group	Fibre optic cable
Product type	Fibre Optic Jumper Cables OM3
Colour	turquoise
Length	10 m

Quantity of fibre	2
Conductor composition	Compact conductor
Cable type	Duplex Cable
External cable	no
Fibre section	Multi mode 50/125µm OM3
Connection ports	LC / LC
Side 1 Connector Type	LC
Side 2 Connector Type	LC
Colour (Cable)	turquoise
Aramid strain relief	yes
External cable diameter	2,8x6 mm
Mantle of external cable	LSOH
Cable LSOH	yes
Max. insertion loss	0.15 dB
Operating temperature min.	-20 °C
Operating temperature max.	70 °C
Storage temperature min.	-40 °C
Storage temperature max.	80 °C
Weight	68.6 g
Height of packaging (single piece)	30 mm
Width of packaging (single piece)	210 mm
Depth of packaging (single piece)	200 mm
Package weight (single piece)	0.091 kg