

ROLINE FO SLIM Jumper Cable 50/125µm OM4, LSOH, LC/LC, OD 1.2mm, violet, 1 m

| | |
|---------------------------|---------------|
| Product No. | 21.15.9261 |
| Manufacturer | ROLINE |
| Manufacturer No. | 21.15.9261 |
| EAN (single piece) | 7611990153299 |



**The solution for space problems in the fiber optic area of your data center!
Extra-thin ROLINE fiber optic patch cables in OM4 quality for high-performance
fiber optic cabling in high-density environments.**

The LC connector with its small cross-section allows high densities in the distribution area. And thanks to the extra-thin cable with a straight 1.2mm diameter, we now also have the appropriate supplement to this connector.

- Security for the future! The OM4 fiber and connector quality with very low insertion ensure an excellent quality at very high bandwidths of up to 10 Gb/s Ethernet, Fibre Channel, and OIF applications to 550 meters - extends the system cost benefits to ultra long building backbones and medium length campus backbones.
- Material and clothing in ROLINE quality
- Outer diameter: 1.2 x 2.4mm
- UPC polish
- Modal Bandwidth: 4700 MHz-km (this bandwidth is based on application-specific implementation of the EMBC requirements)
- Duplex cables with fiber type Multi-mode 50/125µm, OM4

Technical specifications

| | |
|---------------|-------------------|
| Manufacturer | ROLINE |
| Product group | Fibre optic cable |

| | |
|---------------------------------------|-------------------------------|
| Product type | Fibre Optic Jumper Cables OM4 |
| Colour | violet |
| Length | 1 m |
| Quantity of fibre | 2 |
| Conductor composition | Compact conductor |
| Cable type | Duplex Cable |
| External cable | no |
| Fibre section | 50/125µm OM4 |
| Connection ports | LC / LC |
| Side 1 Connector Type | LC |
| Side 2 Connector Type | LC |
| Aramid strain relief | yes |
| External cable diameter | 1.2 x 2.4 mm |
| Mantle of external cable | LSOH |
| Cable LSOH | yes |
| Weight | 9.6 g |
| Height of packaging (single piece) | 10 mm |
| Width of packaging (single piece) | 60 mm |
| Depth of packaging (single piece) | 60 mm |
| Package weight (single piece) | 0.1 kg |