ROLINE FO Jumper Cable Duplex, 50/125μm OM4, LSH/LSH, UPC Polish, LSOH, violet, 5 m

21.15.9495 **Product No.**

ROLINE

Manufacturer No.

Manufacturer

21.15.9495

EAN (single piece) 7611990152872



High-quality fibre optic cable with the high protective, secured LSH connection on both sides - both connections are UPC polished.

- Duplex cable with 50/125µm OM4 fibre type
- Cable material: sheath halogen-free and flame-retardant, violet, solid core with aramid strain relief
- LSH connector: precisely manufactured connector with low return loss, ceramic ferrule, beige
- The LSH connector has a spring-loaded shutter, which fully protects the ferrule from dust and scratches
- UPC Polish (Ultra Physical Contact)
- IL < 0.25dB, RL > 25dB
- IL (typical) < 0.12dB
- Cable OD (outer diameter): 3.0 x 6.0mm

Technical specifications		
Manufacturer	ROLINE	
Product group	Fibre optic cable	
Product type	Fibre Optic Jumper Cables OM4	
Colour	violet	
Length	5 m	

Quantity of fibre2Cable typeDuplex CableExternal cablenoFibre sectionMulti mode 50/125µm OM4Connection portsLSH / LSHSide 1 Connector TypeLSHSide 2 Connector TypeLSHMin. Bending radius, staticSo mmMin. Bending radius, dynamic60 mmAramid strain reliefyesCable LSOHyesFlame retardant according to IEC 60332-1-2yesLow smoke according to IEC 6034-2yesMax. insertion loss0.2 dBMin. return loss30 dBRAL colourRAL 4003 Heather violetWeight87.7 gHeight of packaging (single piece)200 mmWidth of packaging (single piece)200 mmPackage weight (single piece)0.14 kg		
External cable no Fibre section Multi mode 50/125µm OM4 Connection ports LSH / LSH Side 1 Connector Type LSH Min. Bending radius, static Min. Bending radius, dynamic Aramid strain relief yes Cable LSOH yes Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 60332-1-2 Halogen free according to IEC 6034-2 Max. insertion loss 0.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Quantity of fibre	2
Fibre section Multi mode 50/125µm OM4 Connection ports LSH / LSH Side 1 Connector Type LSH Min. Bending radius, static Min. Bending radius, dynamic Aramid strain relief yes Cable LSOH yes Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 60754-2 Max. insertion loss 0.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Cable type	Duplex Cable
Connection ports LSH / LSH Side 1 Connector Type LSH Min. Bending radius, static Min. Bending radius, dynamic Aramid strain relief Cable LSOH Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 60332-1-2 Low smoke according to IEC 60754-2 Max. insertion loss Min. return loss ARAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Peckage weight (single Depth of packaging (single piece) Package weight (single LSH / LSH SH SH SH SH SH SH SH SH SH	External cable	no
Side 1 Connector Type Side 2 Connector Type LSH Min. Bending radius, static Min. Bending radius, dynamic Aramid strain relief Yes Cable LSOH Yes Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 60332-1-2 Low smoke according to IEC 60754-2 Max. insertion loss 0.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Fibre section	Multi mode 50/125µm OM4
Side 2 Connector Type LSH Min. Bending radius, static Min. Bending radius, dynamic Aramid strain relief yes Cable LSOH yes Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 61034-2 Halogen free according to IEC 60754-2 Max. insertion loss 0.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Connection ports	LSH / LSH
Min. Bending radius, static Min. Bending radius, dynamic Aramid strain relief Cable LSOH Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 61034-2 Halogen free according to IEC 60754-2 Max. insertion loss Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Peckage weight (single 0.14 kg	Side 1 Connector Type	LSH
static Min. Bending radius, dynamic Aramid strain relief Cable LSOH Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 60332-2 Halogen free according to IEC 60754-2 Max. insertion loss Min. return loss Min. return loss RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Peckage weight (single 0.14 kg	Side 2 Connector Type	LSH
dynamic Aramid strain relief Cable LSOH yes Flame retardant according to IEC 60332- 1-2 Low smoke according to IEC 61034-2 Halogen free according to IEC 60754-2 Max. insertion loss 0.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg		30 mm
Cable LSOH Yes Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 61034-2 Halogen free according to IEC 60754-2 Max. insertion loss O.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg		60 mm
Flame retardant according to IEC 60332-1-2 Low smoke according to IEC 61034-2 Halogen free according to IEC 60754-2 Max. insertion loss Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Aramid strain relief	yes
according to IEC 60332- 1-2 Low smoke according to IEC 61034-2 Halogen free according to IEC 60754-2 Max. insertion loss 0.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Cable LSOH	yes
Halogen free according to IEC 60754-2 Max. insertion loss O.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	according to IEC 60332-	yes
to IEC 60754-2 Max. insertion loss 0.2 dB Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single) 0.14 kg		yes
Min. return loss 30 dB RAL colour RAL 4003 Heather violet Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg		yes
RAL colour Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Max. insertion loss	0.2 dB
Weight 87.7 g Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Min. return loss	30 dB
Height of packaging (single piece) Width of packaging (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	RAL colour	RAL 4003 Heather violet
(single piece) Width of packaging 200 mm (single piece) Depth of packaging (single piece) Package weight (single 0.14 kg	Weight	87.7 g
(single piece) Depth of packaging 200 mm (single piece) Package weight (single 0.14 kg		30 mm
(single piece) Package weight (single 0.14 kg		200 mm
		200 mm
		0.14 kg