## ROLINE FO Jumper Cable Duplex, 9/125μm, OS2, LSH/LSH, APC Polish, LSOH, yellow, 5 m

**Product No.** 21.15.9505

Designed for Profession

Manufacturer

**ROLINE** 

Manufacturer No.

21.15.9505

**EAN** (single piece)

7611990155149





## High-quality fibre optic cable with the high protective, secured LSH connection on both sides - both connections are APC polished.

- Duplex cable with fiber type 9/125μm OS2
- Cable material: sheath halogen-free and flame-retardant, yellow, solid core with aramid strain relief
- LSH connectors: precision-manufactured connectors with low return loss, APC ground joint, ceramic ferrule
- The LSH connector has a spring-loaded shutter, which fully protects the ferrule from dust and scratches
- APC Polish (8° APC Angled Physical Contact allows tighter connection and smaller endface radii)
- IL < 0.25dB, RL > 60dB
- IL (typical) < 0.12dB
- Cable OD (outer diameter): 3.0 x 6.0mm

| Technical specifications |                   |
|--------------------------|-------------------|
| Manufacturer             | ROLINE            |
| Product group            | Fibre optic cable |

| Product type                               | Fibre Optic Jumper Cables OS2 |
|--|-------------------------------|
| Colour                                     | yellow                        |
| Length                                     | 5 m                           |
| Quantity of fibre                          | 2                             |
| Cable type                                 | Duplex Cable                  |
| External cable                             | no                            |
| Fibre section                              | Single mode 9/125µm OS2       |
| Connection ports                           | LSH / LSH                     |
| Side 1 Connector Type                      | LSH                           |
| Side 2 Connector Type                      | LSH                           |
| Min. Bending radius,<br>static             | 30 mm                         |
| Min. Bending radius,<br>dynamic            | 60 mm                         |
| Aramid strain relief                       | yes                           |
| Cable LSOH                                 | yes                           |
| Flame retardant according to IEC 60332-1-2 | yes                           |
| Low smoke according to IEC 61034-2         | yes                           |
| Halogen free according to IEC 60754-2      | yes                           |
| Max. insertion loss                        | 0.2 dB                        |
| Min. return loss                           | 60 dB                         |
| Weight                                     | 85.7 g                        |
| Height of packaging (single piece)         | 30 mm                         |
| Width of packaging (single piece)          | 200 mm                        |
| Depth of packaging (single piece)          | 200 mm                        |
|  |                               |

Package weight (single 0.14 kg piece)