

# ROLINE Cat.5e (Class D) Modular Coupler, STP, silver

**Product No.**  
**Manufacturer**  
**Manufacturer No.**  
**EAN (single piece)**

21.17.3002  
ROLINE  
21.17.3002  
7611990187973



- The shielded RJ-45 couplers are able to extend Cat. 5e cables
- Best transmission characteristics for pair combination 1/2 and 3/6 (as used by all Ethernet versions)
- Whole housing of metal to safe the signals against electrical and magnetical interferences
- 8 contacts, 1:1 connected
- Colour: silver

| Technical specifications |                           |
|--------------------------|---------------------------|
| Manufacturer             | ROLINE                    |
| Product group            | Connection technology TP  |
| Product type             | RJ-45 Implementing clutch |
| Colour                   | silver                    |
| Shield type              | Screened                  |
| Transfer quality         | Cat5e / Class D           |
| Quantity of ports        | 1                         |
| Assignment               | EIA/TIA 568A              |
| Material (casing)        | metal                     |
| Shield contacts          | yes                       |
| separate strain relief   | no                        |

|                                    |                 |
|------------------------------------|-----------------|
| Connection direction               | Straight        |
| Technical particularity            | 1 : 1 connedted |
| Operating temperature min.         | -10 °C          |
| Operating temperature max.         | 60 °C           |
| Height                             | 22 mm           |
| Width                              | 12 mm           |
| Depth                              | 36 mm           |
| Weight                             | 17.5 g          |
| Height of packaging (single piece) | 20 mm           |
| Width of packaging (single piece)  | 70 mm           |
| Depth of packaging (single piece)  | 100 mm          |
| Package weight (single piece)      | 0.02 kg         |