

ROLINE Cat.5e (Class D) 19" Patch Panel, 24 Ports, STP, black

Product No.	26.11.0328
Manufacturer	ROLINE
Manufacturer No.	26.11.0328
EAN (single piece)	7611990147779



- The panels comply with the EIA / TIA 568 Cat. 5e TSB40A standard
- The cable connection on the back is implemented via LSA-plus connection technology with colour coding on the top in accordance with EIA/TIA 568
- Sheet steel housing and cover
- 24 Ports
- Colour: Black

For a structured cabling system we recommend to use the following components:

- ROLINE Cat.5e S/FTP Cable, Solid Wire, AWG24: 21.15.0019 (100 m), 21.15.0020 (300 m)
- ROLINE Cat.5e Flush/Surface Mount Wall Jack, shielded: 25.16.8487 (white), 25.16.8486 (ivory)/25.16.8387 (white), 25.16.8386 (ivory)
- ROLINE Cat.5e 19" Patch Panel, 24 Ports, shielded: 26.11.0329 (light grey), 26.11.0328 (black)
- ROLINE Cat.5e S/FTP Patch Cord, grey, 5 m: 21.15.0305

Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class D specifications.

Technical specifications	
Manufacturer	ROLINE
Product group	Connection technology TP

Product type	Patchpanel Cat.5e
Colour	black
Shield type	Screened
Transfer quality	Cat5e / Class D
Cabinet system	19"-Technique
Quantity of ports	24
Assembly cable connection	Krone LSAplus
Assignment	EIA/TIA 568A & 568B
Modular assembly	no
Material (casing)	Sheet steel
Shield contacts	Yes
separate strain relief	yes
Connection direction	Straight
Height units	1 U
Height	44 mm
Width	482.6 mm
Depth	136 mm
Weight	1506.2 g
Height of packaging (single piece)	70 mm
Width of packaging (single piece)	150 mm
Depth of packaging (single piece)	570 mm
Package weight (single piece)	1.93 kg