## ROLINE Cat.6 (Class E) 19" Patch Panel, 24 Ports, UTP, grey

**Product No.** 26.11.0355

Designed for Profess

Manufacturer ROLINE

Manufacturer No. 26.11.0355

**EAN (single piece)** 7611990156511







- The ROLINE Cat.6/Class E 19" patch panel fulfils the Cat.6/Class E Permanent Link Standard and is ideal for Gigabit Ethernet networks
- Cable assembly takes place using LSA-plus piercing terminals with colour coding on the top in accordance with EIA/TIA 568
- 24 ports
- Colour: Light grey

For a structured cabling system we recommend to use the following components:

ROLINE Cat.6 UTP Cable, Solid Wire, AWG23: 21.15.0990 (100 m), 21.15.0991 (300 m) ROLINE Cat.6 Flush Mount Wall Jack, unshielded: 25.16.8494 (white), 25.16.8500 (ivory) ROLINE Cat.6 Surface Mount Wall Jack, unshielded: 25.16.8394 (white), 25.16.8395 (ivory) ROLINE Cat.6 19" Patch Panel, 24 Ports, unshielded: 26.11.0355 (light grey), 26.11.0362 (black)

ROLINE Cat.6 UTP Patch Cord, grey, 5 m: 21.15.0935

Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

| Technical specifications |                          |  |
|--------------------------|--------------------------|--|
| Manufacturer             | ROLINE                   |  |
| Product group            | Connection technology TP |  |

| Product type                       | Patchpanel Cat.6 / Class E |
|------------------------------------|----------------------------|
| Colour                             | grey                       |
| Shield type                        | Not screened               |
| Transfer quality                   | Cat6 / Class E             |
| Cabinet system                     | 19"-Technique              |
| Quantity of ports                  | 24                         |
| Assembly cable connection          | Krone LSAplus              |
| Assignment                         | EIA/TIA 568A & 568B        |
| Modular assembly                   | no                         |
| Shield contacts                    | No                         |
| separate strain relief             | yes                        |
| Connection direction               | Straight                   |
| Height units                       | 1 U                        |
| Height                             | 44 mm                      |
| Width                              | 482.6 mm                   |
| Depth                              | 109 mm                     |
| Weight                             | 874.3 g                    |
| Height of packaging (single piece) | 80 mm                      |
| Width of packaging (single piece)  | 150 mm                     |
| Depth of packaging (single piece)  | 490 mm                     |
| Package weight (single piece)      | 2.2 kg                     |