

# ROLINE Keystone Holder, with Cat.6A Keystone, shielded, DIN-Rail, 45°

|                    |               |
|--------------------|---------------|
| Product No.        | 26.11.0379    |
| Manufacturer       | ROLINE        |
| Manufacturer No.   | 26.11.0379    |
| EAN (single piece) | 7630049635692 |



## Keystone holder including shielded Cat.6A keystone, for installation on DIN rail

- Cable access 45° from the top or bottom, connection direction 45° downwards
- With shielded plate (grounding)
- keystones with printed colour coding in accordance with EIA/TIA 568
- Cables can be connected to the keystones without tools – simply place the cable wires in the guides, close the module and press it together – and the connection is complete
- Holder with integrated dust cover
- For cables with outer diameter: 5.0 - 8.0mm
- Suitable for 26AWG (0.40mm) - 22AWG (0.65mm) cables
- Dimensions Keystone Holder: 78.25 x 17.7 x 63.9mm
- Dimensions Keystone: 21.5 x 14.7 x 34.5 mm

| Technical specifications |  |
|--------------------------|--|
| Manufacturer             | ROLINE   |
| Product group            | Connection technology TP   |
| Product type             | DIN rail adapter   |
| Colour                   | grey   |
| Scope of delivery        | DIN-Rail Keystone Holder and Keystone, Installation Guide, Cable Tie |
| Shield type              | Screened   |

|                                    |   |
|------------------------------------|---|
| Transfer quality                   | Cat6A / Class EA  |
| Quantity of ports                  | 1   |
| Assignment                         | EIA/TIA 568A & 568B   |
| Material (casing)                  | ABS + Zinc Alloy  |
| Connection direction               | 45°-inclination   |
| Dimensions (HxWxD)                 | Keystone Holder: 78.25 x 17.7 x 63.9mm, Keystone: 21.5 x 14.7 x 34.5 mm |
| Operating temperature min.         | -10 °C  |
| Operating temperature max.         | 60 °C   |
| Storage temperature min.           | -40 °C  |
| Storage temperature max.           | 70 °C   |
| Height                             | 78.25 mm  |
| Width                              | 17.7 mm   |
| Depth                              | 63.9 mm   |
| Weight                             | 31 g  |
| Height of packaging (single piece) | 0 mm  |
| Width of packaging (single piece)  | 0 mm  |
| Depth of packaging (single piece)  | 0 mm  |
| Package weight (single piece)      | 0 kg  |