


ROLINE 19-inch network cabinet Basic 26 U, 600x600 WxD glass door grey

| | |
|--------------------|---------------|
| Product No. | 26.21.0035 |
| Manufacturer | ROLINE |
| Manufacturer No. | 26.21.0035 |
| EAN (single piece) | 7630049600362 |



ROLINE 19 inch network cabinet Basic 26 U 600x600 WxD glass door grey

The network cabinets in the ROLINE Basic series were developed to enable simple and particularly cost-efficient network expansion. Strategically placed cable inlets ensure effortless installation depending on the application. The cable inlet is located in the base chassis, protected by a screwed cover plate and positioned in the rear centre area. For enclosures from 800 mm width, additional cable inlets with plastic covers are added on the left and right. These are also integrated in the roof (once for 600 mm enclosure width, three times for 800 mm enclosure width). The roof chassis also has a punched-out area for the installation of a fan module. Two pairs of galvanised 19" profile rails are installed inside, which can be read in both directions and can be adjusted in depth. They are also connected to additional depth struts in the enclosure. Each cabinet consists of a robust steel construction with a material thickness of up to 1.5 mm sheet steel.

The colouring is done using electrostatic powder coating in the standard colours grey (RAL 7035) and black (RAL 9005). Removable side and rear panels as well as a lockable and removable front door improve accessibility. It is possible to change the door hinge. Thanks to their demountable design, the cabinets can also be completely dismantled if required.

| Technical specifications | |
|--------------------------|-------------------|
| Manufacturer | ROLINE |
| Product group | 19"/-10"-Cabinet |
| Product type | 19"-Floor cabinet |

| | |
|------------------------------|--|
| Colour | grey |
| Scope of delivery | 19-inch network enclosure Basic 26 U, earthing cable set, installation set (screws, cage nuts, washers), 2x spanners, instructions |
| Type of profile rail | L-shaped |
| Modular spacing | 482.6 mm (19 inch) |
| Model | With permanent frame |
| Height units | 26 U |
| Minimum rack depth supported | 290 mm |
| Maximum rack depth supported | 550 mm |
| delivery condition | fully assembled |
| Material group | Steel |
| Material front door | Glass |
| Wall mountable | no |
| Demountable | yes |
| Adjustable feets | yes |
| Maximum weight capacity | 600 kg |
| Protection class (IP Code) | IP20 |
| Soundproof | no |
| Number of doors | 1 |
| With front door | yes |
| With backside door | no |
| With glazed door | yes |
| Front | Glass door |
| Rack rails | yes |
| Roof | Roof not removable (fixed) |
| Side panels included | yes |

| | |
|---------------------------------------|------------------------|
| Removeable side panels | yes |
| Removable front door | yes |
| Removable back door | yes |
| Floor | Base plate punched out |
| Ventilation | Passive |
| RAL colour | RAL 7035 Light grey |
| Height | 1300 mm |
| Width | 600 mm |
| Depth | 600 mm |
| Weight | 53 kg |
| Height of packaging (single piece) | 1440 mm |
| Width of packaging (single piece) | 680 mm |
| Depth of packaging (single piece) | 680 mm |
| Package weight (single piece) | 56.4 kg |